[File 60] **ANTE: Abstracts in New Tech & Engineer** 1966-2007/Jul
(c) 2007 CSA. All rights reserved.
[File 56] **Computer and Information Systems Abstracts** 1966-2007/Aug
(c) 2007 CSA. All rights reserved.
[File 35] **Dissertation Abs Online** 1861-2007/Jul
(c) 2007 ProQuest Info&Learning. All rights reserved.
[File 8] **Ei Compendex(R)** 1884-2007/Aug W1
(c) 2007 Elsevier Eng. Info. Inc. All rights reserved.
[File 266] **FEDRIP** 2007/Jul
Comp & dist by NTIS, Intl Copyright All Rights Res. All rights reserved.
[File 583] **Gale Group Globalbase(TM)** 1986-2002/Dec 13
(c) 2002 The Gale Group. All rights reserved.
File 583: This file is no longer updating as of 12-13-2002.
[File 65] **Inside Conferences** 1993-2007/Aug 15
(c) 2007 BLDSC all rts. reserv. All rights reserved.
[File 2] **INSPEC** 1898-2007/Aug W1
(c) 2007 Institution of Electrical Engineers. All rights reserved.
[File 6] **NTIS** 1964-2007/Aug W3
(c) 2007 NTIS, Intl Cpyrght All Rights Res. All rights reserved.
[File 144] **Pascal** 1973-2007/Jul W5
(c) 2007 INIST/CNRS. All rights reserved.
[File 34] **SciSearch(R) Cited Ref Sci** 1990-2007/Aug W3
(c) 2007 The Thomson Corp. All rights reserved.
[File 434] **SciSearch(R) Cited Ref Sci** 1974-1989/Dec
(c) 2006 The Thomson Corp. All rights reserved.
[File 256] **TecInfoSource** 82-2007/Nov
(c) 2007 Info.Sources Inc. All rights reserved.
[File 95] **TEME-Technology & Management** 1989-2007/Aug W2
(c) 2007 FIZ TECHNIK. All rights reserved.
[File 99] **Wilson Appl. Sci & Tech Abs** 1983-2007/Jul
(c) 2007 The HW Wilson Co. All rights reserved.

Set   Items   Description
S1   4805   S (STEINER(1W)(TREE? ? OR NODE OR POINT? ? OR VERTICE? ?)) OR (S()STEINER(1W)(TREE? ?
OR NODE OR POINT? ? OR VERTICE? ?)) OR NASH()WILLIAMS()TUTTE(2N)THEOR????? OR
((NASH(1W)WILLIAMS(1W)TUTTE)(2N)THEOR?????)
S2   6299   S ((STEINER(1W)TREE? ? OR TREE? ? OR NODE OR POINT? ? OR VERTICE? ?)(5N)(SET OR
SUBSET OR SUB()SET))(10N)(NODE OR STRUCTURE? ?)
S3   281340   S ((STEINER(1W)TREE? ? OR TREE? ? OR NODE OR POINT? ? OR VERTICE? ?)(10N)(CLIENT? ?
OR ENTIT??? OR NODE))
S4   291   S S1(20N)(CREAT??? OR GENERAT???)
S5   347   S (S1(10N)(MERG??? OR PACK??? OR TOGETHER OR MIX??? OR BLEND??? OR BINDING OR
BOUND OR COMBIN??? OR CONSOLIDAT??? OR COMPRESS??? OR CONDENS??? OR JOIN?????))
S6   203   RD (unique items)
S7   250   S (S1(5N)(MERG??? OR PACK??? OR TOGETHER OR MIX??? OR BLEND??? OR BINDING OR BOUND
OR COMBIN??? OR CONSOLIDAT??? OR COMPRESS??? OR CONDENS??? OR JOIN?????))
S8   4444   S (STEINER(1W)TREE? ?)
S9   143   S (S8(5N)(MERG??? OR PACK??? OR TOGETHER OR BINDING OR COMBIN??? OR CONSOLIDAT???
OR JOIN?????))
S10   78   RD (unique items)
S11   0   S S10 AND AC=US/PR AND AY=(1963:2003)/PR
S12   0   S S10 AND AC=US AND AY=1963:2003
S13   0   S S10 AND AC=US AND AY=(1963:2003)/PR
S14   54   S S10 AND PY=1963:2003
S15   0   S S10 AND NOTPY=2003:2007
S16   47   S S10 NOT PY=2003:2007
S17   0   S S16 AND (AU=(JAIN, K? OR JAIN K?))
S18   0   S S16 AND (AU=(MAHDIAN, M? OR MAHDIAN M?))
S19   0   S S16 AND (AU=(SALAVATIPOUR, M? OR SALAVATIPOUR M?))

Higher relevance

d

Subject summary

Symbolic generation of constrained random logic cells
Costa, R; Curatelli, F; Caviglia, D D; Bisio, G M
Abstract:
A symbolic cell generator (SYC) that can generate the symbolic layout of a generic CMOS logic cell is presented. It accepts as input a SPICE-like netlist describing circuit components, connectivity, and the list of the I/O pins. Using this generator, the user can specify topological constraints on pin and transistor positions, the maximum lengths of polysilicon and diffusion wires, and a preferred layer for each electrical node. Cells are generated according to optimization criteria that take into account not only geometric factors, such as cell area, aspect ratio, and wirelength, but also electrical features, namely capacitance to the substrate and contact and via minimization. The generator's placement strategy includes transistor clustering into regions, global region placement by linear ordering, and two-dimensional local transistor placement. The routing **combines Steiner trees** and Lee algorithms. Object-oriented programming paradigms were used in the implementation of the program, written in C language. Experimental results for small and medium-sized cells are presented
Descriptors: Semiconductor devices; Generators; Transistors; Placement; Optimization; Logic; Constraints; Diffusion layers; Clustering; Capacitance; Integrated circuits; Circuits; Trees; Lists; Object-oriented programming; C (programming language); Criteria; Electric wire; Aspect ratio; Minimization
Subj Catg: 81, Engineering and Sciences
Abstract:
...regions, global region placement by linear ordering, and two-dimensional local transistor placement. The routing **combines Steiner trees** and Lee algorithms. Object-oriented programming paradigms were used in the implementation of the program...

Near-optimal critical sink routing tree constructions
Boese, K D; Kahng, A B; McCoy, B A; Robins, G
Abstract:
We present critical-sink routing tree (CSRT) constructions which exploit available critical-path information to yield high-performance routing trees. Our CS-Steiner and "global slack removal" algorithms **together** modify traditional **Steiner tree** constructions to optimize signal delay at identified critical sinks. We further propose an iterative Elmore routing tree (ERT) construction which optimizes Elmore delay directly, as opposed to heuristically abstracting linear or Elmore delay as in previous approaches. Extensive timing simulations on industry IC and MCM interconnect parameters show that our methods yield trees that significantly improve (by averages of up to 67%) over minimum Steiner routings in terms of delays to identified critical sinks. ERTs also serve as generic high-performance routing trees when no critical sink is specified: for 8-sink nets in standard IC (MCM) technology, we improve average sink delay by 19% (62%) and maximum sink delay by 22% (52%) over the minimum Steiner routing. These approaches provide simple, basic advances over

existing performance-driven routing tree constructions. Our results are complemented by a detailed analysis of the accuracy and fidelity of the Elmore delay approximation; we also exactly assess the suboptimality of our heuristic tree constructions. In achieving the latter result, we develop a new characterization of Elmore-optimal routing trees, as well as a decomposition theorem for optimal Steiner trees, which are of independent interest

Descriptors: Trees; Construction; Delay; Integrated circuits; Construction industry; Heuristic; Accuracy; Time measurements; Optimization; Theorems; Computer simulation; Signal delay; Approximation; Mathematical analysis; Decomposition; Standards; Algorithms; Iterative methods; Computer aided design; Design engineering
Subj Catg: 81, Engineering and Sciences
Abstract:
...information to yield high-performance routing trees. Our CS-Steiner and "global slack removal" algorithms **together** modify traditional **Steiner tree** constructions to optimize signal delay at identified critical sinks. We further propose an iterative Elmore...

16/5,K/3 (Item 3 from file: 56) <u>Links</u>
   Fulltext available through: <u>USPTO Full Text Retrieval Options</u>
Computer and Information Systems Abstracts
(c) 2007 CSA. All rights reserved.
0000263859   IP Accession No: 0170623
General approximation technique for constrained forest problems
Goemans, Michel X; Williamson, David P Massachusetts Inst of Technology, Cambridge, MA, USA
SIAM J COMPUT , v 24 , n 2 , p 296-317 , 1995
Publication Date: 1995
Publisher: SOCIETY FOR INDUSTRIAL AND APPLIED MATHEMATICS , 3600 University City Science Center ,
Philadelphia , PA , 19104-2688
Country Of Publication: USA
Publisher Url: http://epubs.siam.org
Publisher Email: siam@siam.org
Document Type: Journal Article
Record Type: Abstract
Language: English
ISSN: 0097-5397
File Segment: Computer & Information Systems Abstracts
Abstract:
A general approximation technique for graph-related optimization problems involving an integer program (IP) is proposed. Such graph-related problem is referred to as constraint forest problem. The proposed technique can be applied to problems of covering vertices of graphs with trees, cycles or paths satisfying certain requirements at minimum cost. The algorithm produced from this technique can run in $O(n^{2}\log n)$ time and come within a factor of two of optimal for most optimization problems.
Descriptors: Optimization; Graph theory; Algorithms; Trees (mathematics); Combinatorial mathematics; Polynomials; Computational complexity; Integer programming; Set theory; Constraint theory; Linear programming; Functions
Identifiers: Constrained forest problems; Matching; **Steiner tree** problem ; T **joins**; Traveling salesman problem
Subj Catg: C 921.6, Numerical Methods; C 921.5, Optimization Techniques; C 921.4, Combinatorial Mathematics (Includes Graph Theory, Set Theory); C 921.1, Algebra; C 721.1, Computer Theory (Includes Formal Logic, Automata Theory, Switching Theory, Programming Theory)
Identifiers: Constrained forest problems; Matching; **Steiner tree** problem ; T **joins**; Traveling salesman problem

16/5,K/4 (Item 4 from file: 56) <u>Links</u>
   Fulltext available through: <u>USPTO Full Text Retrieval Options</u>
Computer and Information Systems Abstracts
(c) 2007 CSA. All rights reserved.
0000215900   IP Accession No: 2736465
A note on lower bounds for rectilinear Steiner trees.
Salowe, J S Dep. Comp. Sci., Univ. Virginia, Charlottesville, VA 22903, USA
Information Processing Letters , v 42 , n 3 , p 151-152 , 1992
Publication Date: 1992
Publisher: Elsevier Science BV , P.O. Box 211 , Amsterdam , 1000 AE
Country Of Publication: Netherlands
Publisher Url: http://www.elsevier.com
Publisher Email: w.tukker@elsevier.nl
Document Type: Journal Article
Record Type: Citation
Language: English
ISSN: 0020-0190
File Segment: Computer & Information Systems Abstracts
Descriptors: Data structure; **Steiner trees**; **Sphere packing**
Subj Catg: C CS1.8, PROGRAMMING METHODS
Descriptors: Data structure; **Steiner trees**; **Sphere packing**

16/5,K/5 (Item 5 from file: 56) <u>Links</u>
   Fulltext available through: <u>ScienceDirect</u>

Computer and Information Systems Abstracts
0000139699   IP Accession No: 1893857
Edge-packing of graphs and network reliability.
Colbourn, C J Dep. Comp. Sci., Univ. Auckland, Auckland, New Zealand
DISCRETE MATH. , v 72 , n 1-3 , p 49-61 , 1988
Publication Date: 1988
Conference:
1. Japan Conference of Graph Theory and Applications , Hakone (Japan) , 1-5 June 1986
Document Type: Conference Paper; Journal Article
Record Type: Abstract
Language: English
File Segment: Computer & Information Systems Abstracts
Abstract:
The reliability of a network can be efficiently bounded using graph-theoretical techniques based on edge-packing. We examine the application of combinatorial theorems in edge-packing spanning trees, s, t-paths, and s, t-cuts to the determination of reliability bounds. We compare the resulting bounds with known bounds produced by different techniques, and establish that the edge-packing bounds often produce a substantial improvement. We also establish that three other edge-packing problems arising in reliability bounding are NP-complete, namely edge- packing by networks cutsets, **Steiner trees**, and Steiner cutsets.
Descriptors: Networks; Reliability; Graph theory; Np completeness
Identifiers: edge packing
Subj Catg: C CM5.6, GRAPH THEORY
Abstract:
...that three other edge-packing problems arising in reliability bounding are NP-complete, namely edge-**packing** by networks cutsets, **Steiner trees**, and Steiner cutsets.

16/5,K/6 (Item 6 from file: 56) Links
    Fulltext available through: ScienceDirect
Computer and Information Systems Abstracts
0000098945   IP Accession No: 1195706
WEAVER: An application of knowledge-based expert systems to detailed routing of VLSI circuits.
Joobbani, R Carnegie-Mellon Univ., Pittsburgh, PA 15213, USA
Addl. Source Info: Dissertation Abstracts International Part B: Science and Engineering [DISS. ABST. INT. PT. B - SCI. & ENG.], vol. 46, no. 5, 1985, 173 pp
Publication Date: 1985
Record Type: Abstract
Language: English
Notes: Order No. FAD DA8513683
File Segment: Computer & Information Systems Abstracts
Abstract:
This thesis presents background about some representative techniques for routing and summarizes their characteristics. It then studies in detail the different factors (such as minimum area, number of vias, wire length, etc.) that affect the routing quality, and the different criteria (such as vertical/horizontal constraint graph, **merging**, minimal rectilinear **Steiner tree**, etc.) that can be used to optimize these factors.
Descriptors: Very large scale integration; Design; Optimization; Computer aided design; Artificial intelligence; Weaver; Microelectronics; Routing; Vlsi (very large scale integration); Expert systems
Identifiers: dissertation
Subj Catg: E ED20.4, HYBRID UNITS; C CA2.1, GENERAL-ARTIFICIAL INTELLIGENCE; C CA19.4, ELECTRONIC DEVICES
Abstract:
...that affect the routing quality, and the different criteria (such as vertical/horizontal constraint graph, **merging**, minimal rectilinear **Steiner tree**, etc.) that can be used to optimize these factors.

16/5,K/7 (Item 1 from file: 35) Links
Dissertation Abs Online
01674575 ORDER NO: AADMQ-31387
OPTIMAL NETWORK DESIGN FOR NATURAL GAS PIPELINES
Author: DOTT, DAWN ROBIN
Degree: M.SC.
Year: 1998
Corporate Source/Institution: UNIVERSITY OF CALGARY (CANADA) (0026)
Adviser: S. C. WIRASINGHE
Source: Volume 37/02 of MASTERS ABSTRACTS. of Dissertations Abstracts International.
PAGE 652 . 117 PAGES
Descriptors: ENGINEERING, CIVIL ; ENGINEERING, PETROLEUM ; ENERGY
Descriptor Codes: 0543; 0765; 0791
ISBN: 0-612-31387-5

Natural gas transportation requires a continuous pipeline network from well-head to burner-tip. This work applies analytical network analysis techniques to the pipeline network design problem. Four issues receive attention: (1) central facility density, (2) spatially-optimal network design, (3) central facility placement, and (4) impact of environment on pipeline design. The first of these problems is solved using a market area model. Here, an appropriate configuration factor for pipeline networks is determined and used to calculate optimal density. Second, concepts of the minimal spanning tree and **Steiner trees** are **combined** in an analytical algorithm for generating near-optimal pipeline networks. Third, a standard optimisation process locates the network median for optimal facility placement. Last, monetary valuation of the environment is shown to have relevance to pipeline projects, and a revealed preference technique is proposed. Case studies of several Alberta pipeline networks illustrate the network concepts presented.

...determined and used to calculate optimal density. Second, concepts of the minimal spanning tree and **Steiner trees** are **combined** in an analytical algorithm for generating near-optimal pipeline networks. Third, a standard optimisation process...

16/5,K/8 (Item 2 from file: 35) <u>Links</u>
Dissertation Abs Online
01486513 ORDER NO: AADAA-I9616130
CONSTRAINT-DRIVEN GLOBAL ROUTERS (ANALOG LAYOUT, NETWORKS)
Author: AL-MANSOORI, WAFA A.
Degree: PH.D.
Year: 1996
Corporate Source/Institution: TUFTS UNIVERSITY (0234)
Adviser: KRISHNAMURTHY SOUMYANATH
Source: Volume 5702B of Dissertations Abstracts International.
PAGE 1296 . 114 PAGES
Descriptors: ENGINEERING, ELECTRONICS AND ELECTRICAL
Descriptor Codes: 0544

In this dissertation we address the signal routing problem for fully differential nets in mixed analog-digital circuits and critical digital nets on integrated circuits. We formally define the fully differential net routing problem as an electrical matching problem. The proposed router is a gridless constraint-driven global router for fully differential terminals which are placed symmetrically about an imaginary axis. Depending on the required circuit performance, two positive parameters ϵ_{r} and ϵ_{c} are used to maintain resistance and capacitance mismatch within acceptable limits. The router matches the net-pair parasitics segment by segment while minimizing a cost function designed for differential signals. The common-mode rejection of crosstalk is included in the cost function and the matching criteria. Using a search technique derived from AI applications (the A* algorithm), both lumped resistance and capacitance are matched. In addition, this technique permits the relaxation of symmetry restriction during the placement phase.

In the case of critical digital nets, a gridless contraint-driven router is proposed. Given a delay bound $t_{max_{i}}$ for each sink terminal, the router minimizes the combined signal delay to the terminals while simultaneously satisfying each individual delay bound. When compared to minimum **Steiner tree** routers, our router decreased the **combined** delay up to 30%. The maximum signal delay of each net was also improved up to 37% and the net skew was minimized. .

...delay to the terminals while simultaneously satisfying each individual delay bound. When compared to minimum **Steiner tree** routers, our router decreased the **combined** delay up to 30%. The maximum signal delay of each net was also improved up...

16/5,K/9 (Item 3 from file: 35) <u>Links</u>
Dissertation Abs Online
01350063 ORDER NO: NOT AVAILABLE FROM UNIVERSITY MICROFILMS INT'L.
ON THE DESIGN OF APPROXIMATION ALGORITHMS FOR A CLASS OF GRAPH PROBLEMS (OPTIMIZATION)
Author: WILLIAMSON, DAVID PAUL
Degree: PH.D.
Year: 1993
Corporate Source/Institution: MASSACHUSETTS INSTITUTE OF TECHNOLOGY (0753)
Supervisor: MICHEL X. GOEMANS
Source: Volume 5411B of Dissertations Abstracts International.
PAGE 5787 .
Descriptors: COMPUTER SCIENCE; MATHEMATICS; OPERATIONS RESEARCH
Descriptor Codes: 0984; 0405; 0796

In this thesis, we present a single technique for approximating a large class of graph problems. The technique is based on the standard primal-dual method, and shows the importance of this method in designing approximation algorithms.

The class of problems we consider involves selecting a minimum-cost set of edges such that at least f(S) edges have exactly one endpoint in each subset of vertices S, for certain easily characterized functions f. We show that our technique leads to $2{\cal H}(f_{\rm max})$-approximation algorithms for problems in this class, where $f_{\rm max} = max_{s} f(S)$ and ${\cal H}(k)$ is the harmonic function $1 + {1\over2} + \... + {1\over k}.$ The class captures a wide variety of classical and complex problems in combinatorial optimization, including the minimum-cost spanning tree, Steiner tree, generalized **Steiner tree**, survivable network design, T-**join**, minimum-weight perfect matching (under triangle inequality), two-matching (under triangle inequality), and location-design problems. Our algorithm runs in $O(n\sp2m\sp\prime f_{\rm max} + n\sp2\omega_{f}f_{\rm max})$ time on a graph of n vertices and m edges, where $m\sp\prime = min(nf_{\rm max}, m)$ and ω_{f} is the time to compute the function f. We obtain faster time bounds for specific problems of interest.

The algorithms produced first generalize classical algorithms for minimum-cost spanning trees and shortest paths. Second, they provide approximation algorithms for problems in P (such as the minimum-weight perfect matching problem under triangle inequality) that run asymptotically faster than the best-known algorithms that solve these problems exactly. Third, they provide approximation algorithms for problems which had no previously known approximation algorithm. For instance, the technique gives the first approximation algorithm for the survivable network design problem, which is the problem of finding a minimum-cost set of edges such that there are $r\sb{ij}$ edge-disjoint paths between each pair of vertices i and j. Fourth, the algorithms given by the technique improve on the running time and/or the approximation factor of several known approximation algorithms.

Extensions of the main technique of this thesis lead to approximation algorithms for problems which do not fall in the class of problems mentioned above. For example, we give a 2-approximation algorithm for the prize-collecting traveling salesman problem and a $2{\cal H}(k)$- approximation algorithm for the minimum-cost k-vertex-connected subgraph problem.

Finally, we conduct an experimental study of our 2-approximation algorithm for minimum-weight perfect matching on Euclidean instances. We present computational results for both random and real-world instances having between 1,000 and 131,072 vertices. The results indicate that our algorithm generates a matching within 2% of optimality in most cases. In over 1,400 experiments, the algorithm was never more than 4% from optimal. (Copies available exclusively from MIT Libraries, Rm. 14-0551, Cambridge, MA 02139-4307. Ph. 617-253-5668; Fax 617-253-1690.) (Abstract shortened by UMI.)

...and complex problems in combinatorial optimization, including the minimum-cost spanning tree, Steiner tree, generalized **Steiner** tree, survivable network design, T-**join**, minimum-weight perfect matching (under triangle inequality), two-matching (under triangle inequality), and location-design...

16/5,K/10 (Item 4 from file: 35) <u>Links</u>
Dissertation Abs Online
887218 ORDER NO: AAD85-13683
WEAVER: AN APPLICATION OF KNOWLEDGE-BASED EXPERT SYSTEMS TO DETAILED ROUTING OF VLSI CIRCUITS (DESIGN, ROUTING)
Author: JOOBBANI, ROSTAM
Degree: PH.D.
Year: 1985
Corporate Source/Institution: CARNEGIE-MELLON UNIVERSITY (0041)
Source: Volume 4605B of Dissertations Abstracts International.
PAGE 1617 . 173 PAGES
Descriptors: COMPUTER SCIENCE
Descriptor Codes: 0984

Routing of VLSI chips is an important, time consuming, and difficult problem. The difficulty of the problem is attributed to the large number of often conflicting factors that affect the routing quality. Traditional techniques have approached routing by ignoring some of these factors and imposing unnecessary constraints in order to make routing tractable. In addition to the imposition of these restrictions, which simplify the problems to a degree but at the same time reduce the routing quality, traditional approaches use brute force. They often transform the problem into mathematical or graph problems and completely ignore the specific knowledge about the routing task that can greatly help the solution.

This thesis overcomes some of the above problems and presents a system that performs routing close to what human designers do. In other words it heavily capitalizes on the knowledge of human expertise in this area, it does not impose unnecessary constraints, it considers all the different factors that affect the routing quality, and most importantly it allows constant user interaction throughout the routing process.

To achieve the above, this thesis presents background about some representative techniques for routing and summarizes their characteristics. It then studies in detail the different factors (such as minimum area, number of vias, wire length, etc.) that affect the routing quality, and the different criteria (such as vertical/horizontal constraint graph, **merging**, minimal rectilinear **Steiner** tree, etc.) that can be used to optimize these factors.

The result of the above study is then used to implement WEAVER, a knowledge-based routing expert. To evaluate the effectiveness of the approach, a number of experiments are performed which compare WEAVER's performance with the traditional approaches. These experiments show: a dramatic improvement over the traditional approaches; a performance equal to or better than human expertise; the effectiveness of the use of human knowledge; and the viability of the technique of knowledge-based expert systems in the routing domain, the foundation on which WEAVER is based.

...that affect the routing quality, and the different criteria (such as vertical/horizontal constraint graph, **merging**, minimal rectilinear **Steiner** tree, etc.) that can be used to optimize these factors.
The result of the above study...

16/5,K/11 (Item 1 from file: 8) <u>Links</u>
Fulltext available through: <u>USPTO Full Text Retrieval Options</u>
Ei Compendex(R)
09129097   **E.I. No:** EIP02377082143
Title: Routing strategies for multicast packet radio networks
Author: Hemminger, Thomas L.; Coulston, Chris; Pomalaza-Raez, Carlos A.
Corporate Source: Sch. of Eng. and Eng. Technology Penn State University Behrend College, Erie, PA 16563, United States
Source: International Journal of Smart Engineering System Design v 4 n 3 July/September 2002. p 215-223

Abstract: A common problem in a packet radio network (PRN) environment is to construct a multicasting network from a single source to a set of remote destinations which minimizes the number of transmissions. This problem is known to be NP-complete, thus computing an optimal solution may be infeasible for sizable networks. This paper provides two alternative solutions to this problem. The first is a heuristic algorithm which iteratively builds a spanning tree from the destinations to the source. A second solution, included for comparative purposes, is based on the Hopfield neural network whose dynamics are governed by a motion equation and a set of constraints. Both solutions are tested on a variety of instances against an optimal algorithm. Results show the approaches form good solutions (the number of transmissions is within about 3% of the optimum) and run in a fraction of the time required to form the optimal solution. 22 Refs.
Descriptors: *Packet networks; Multicasting; Routers; Optimization; Heuristic methods; Iterative methods; Neural networks; Constraint theory; Problem solving; Algorithms
Identifiers: Multicast packet radio networks (PRN); Steiner minimal tree (SMT) problems
  Classification Codes:
721.1 (Computer Theory (Includes Formal Logic, Automata Theory, Switching Theory & Programming Theory)); 722.3 (Data Communication, Equipment & Techniques); 921.5 (Optimization Techniques); 921.6 (Numerical Methods); 723.4 (Artificial Intelligence)
721 (Computer Circuits & Logic Elements); 716 (Electronic Equipment, Radar, Radio & Television); 717 (Electro-Optical Communication); 718 (Telephone & Other Line Communications); 722 (Computer Hardware); 921 (Applied Mathematics); 723 (Computer Software, Data Handling & Applications)
72 (COMPUTERS & DATA PROCESSING); 71 (ELECTRONICS & COMMUNICATION ENGINEERING); 92 (ENGINEERING MATHEMATICS)
Identifiers: Multicast packet radio networks (PRN); Steiner minimal tree (SMT) problems

  16/5,K/12 (Item 2 from file: 8) Links
    Fulltext available through: ScienceDirect
Ei Compendex(R)
09127004 E.I. No: EIP02377076628
Title: Effective location-guided tree construction algorithms for small group multicast in MANET
Author: Chen, Kai; Nahrstedt, Klara
Corporate Source: Computer Science Department Univ. Illinois at Urbana-Champaign, Urbana, IL 61801, United States
Conference Title: IEEE Infocom 2002
Conference Location: New York, NY, United States   Conference Date: 20020623-20020627
Sponsor: IEEE
E.I. Conference No.: 59460
Abstract: Group communication has become increasingly important in mobile ad hoc networks (MANET). Current multicast routing protocols in MANET have been shown to have large overhead due to dynamic network topology. To overcome this problem, there is a recent shift towards stateless multicast in small groups (DDM left bracket 1 right bracket). DDM queries the underlying unicast routing protocol to forward data packets towards members of a multicast group. The multicast distribution tree in DDM is implicit and cannot be controlled by the upper transport and application layers. In this paper, we introduce another small group multicast scheme, based on packet encapsulation, which uses novel packet distribution tree construction algorithms for efficient data delivery. The packet distribution tree is constructed explicitly with the goal of minimizing the overall bandwidth cost of the tree. The tree construction algorithms include a location-guided k-ary (LGK) tree and a location-guided Steiner (LGS) tree. Both of them utilize the geometric locations of the destination nodes as heuristics to compute the trees, and are accompanied by a hybrid location update mechanism to disseminate location information among a group of nodes. Our simulation results show that LGS tree has lower bandwidth cost than LGK tree when the location information of the nodes is up-to-date, and its cost is similar to that of an optimal Steiner multicast tree. When location information of the nodes is out-dated, LGK tree outperforms LGS tree due to its lower computational complexity. 24 Refs.
Descriptors: *Multicasting; Mobile telecommunication systems; Information dissemination; Algorithms; Trees (mathematics); Network protocols; Packet switching; Geometry; Heuristic methods; Computer simulation; Computational complexity; Optimization
Identifiers: Mobile ad hoc networks; Group communication; Tree construction algorithm; Location update mechanism; Steiner tree; Packet encapsulation; Packet distribution tree
  Classification Codes:
716.1 (Information & Communication Theory); 716.3 (Radio Systems & Equipment); 903.2 (Information Dissemination); 723.1 (Computer Programming); 921.4 (Combinatorial Mathematics, Includes Graph Theory, Set Theory); 723.5 (Computer Applications)
716 (Electronic Equipment, Radar, Radio & Television); 903 (Information Science); 723 (Computer Software, Data Handling & Applications); 921 (Applied Mathematics)

71 (ELECTRONICS & COMMUNICATION ENGINEERING); 90 (ENGINEERING, GENERAL); 72 (COMPUTERS & DATA PROCESSING); 92 (ENGINEERING MATHEMATICS)
Identifiers: Mobile ad hoc networks; Group communication; Tree construction algorithm; Location update mechanism; Steiner tree; Packet encapsulation; Packet distribution tree

16/5,K/13 (Item 3 from file: 8) <u>Links</u>
    Fulltext available through: <u>ScienceDirect</u>
Ei Compendex(R)
09087731   E.I. No: EIP02287010887
Title: A genetic approach to analog module placement with simulated annealing
Author: Zhang, Lihong; Kleine, Ulrich
Corporate Source: Institute for Electronics Signal Processing and Commun. (IESK) Otto-von-Guericke Univ. of Magdeburg, D-39016 Magdeburg, Germany
Conference Title: 2002 IEEE International Symposium on Circuits and Systems
Conference Location: Phoenix, AZ, United States   Conference Date: 20020526-20020529
Sponsor: IEEE
E.I. Conference No.: 59247
Source: Proceedings - IEEE International Symposium on Circuits and Systems v 1 2002. p I/345-I/348 (IEEE cat n 02ch37353)
Publication Year: 2002
CODEN: PICSDI   ISSN: 0271-4310
Language: English
Document Type: CA; (Conference Article)   Treatment: T; (Theoretical); X; (Experimental)
Journal Announcement: 0207W2
Abstract: This paper presents a novel approach to analog module placement with the combination of genetic algorithm and simulated annealing. The approach is based on the bottom-left relative placement represented by binary tree. It is superior to the other three approaches which were implemented with pure simulated annealing or genetic algorithms. A fractional factorial experiment was conducted using an orthogonal array to study the algorithm parameters. A meta-GA was applied to determine the exact parameter values. The dedicated cost function covers the special requirements of analog integrated circuits. The experimental results show this promising algorithm makes the best performance with the least mean cost and standard deviation over all the other compared approaches. 12 Refs.
Descriptors: *Integrated circuit layout; Linear integrated circuits; Computer aided design; Genetic algorithms; Simulated annealing; Trees (mathematics); Parameter estimation; Heuristic methods; MOS devices; Computer simulation
Identifiers: Analog module placement; Analog integrated circuits; Bottom left relative placement; Software package ALADIN; Binary tree; Steiner tree problem; Cost function
  Classification Codes:
714.2 (Semiconductor Devices & Integrated Circuits); 723.5 (Computer Applications); 723.1 (Computer Programming); 921.5 (Optimization Techniques); 921.4 (Combinatorial Mathematics, Includes Graph Theory, Set Theory); 921.6 (Numerical Methods)
714 (Electronic Components & Tubes); 723 (Computer Software, Data Handling & Applications); 921 (Applied Mathematics)
71 (ELECTRONICS & COMMUNICATION ENGINEERING); 72 (COMPUTERS & DATA PROCESSING); 92 (ENGINEERING MATHEMATICS)
Identifiers: Analog module placement; Analog integrated circuits; Bottom left relative placement; Software package ALADIN; Binary tree; Steiner tree problem; Cost function

16/5,K/14 (Item 4 from file: 8) <u>Links</u>
    Fulltext available through: <u>USPTO Full Text Retrieval Options</u>
Ei Compendex(R)
09017838   E.I. No: EIP02116883543
Title: Buffered Steiner trees for difficult instances
Author: Sullivan, A.J.; Alpert, Charles J.; Gandham, Gopal; Hrkic, Milos; Hu, Jiang ; Kahng, Andrew B.; Lillis, John; Liu, Bao; Quay, Stephen T.; Sapatnekar, Sachin S.
Corporate Source: IBM Corporation, Austin, TX 78758, United States
Source: IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems v 21 n 1 January 2002. p 3-14
Publication Year: 2002
CODEN: ITCSDI   ISSN: 0278-0070
Language: English
Document Type: JA; (Journal Article)   Treatment: T; (Theoretical)
Journal Announcement: 0203W3
Abstract: With the rapid scaling of integrated-circuit technology, buffer insertion has become an increasingly critical optimization technique in high-performance design. The problem of finding a buffered Steiner tree with optimal delay characteristics has been an active area of research and excellent solutions exist for most instances. However, there exists a class of real "difficult" instances, which are characterized by a large number of sinks (e.g., 20-100), large variations in sink criticalities, nonuniform sink distribution, and varying polarity requirements. Existing techniques are either inefficient, wasteful of buffering resources, or unable to find a high-quality solution. We propose C-tree, a two-level construction that first clusters sinks with common characteristics together, constructs low-level Steiner trees for each cluster, then performs a timing-driven Steiner construction on the top-level clustering. We show that this hierarchical approach can

achieve higher quality solutions with fewer resources compared to traditional timing-driven Steiner trees. 23 Refs.
Descriptors: *Integrated circuit layout; Trees (mathematics); Electric network topology; Interconnection networks; Optimization
Identifiers: Buffered Steiner trees
Classification Codes:
714.2 (Semiconductor Devices & Integrated Circuits); 921.4 (Combinatorial Mathematics, Includes Graph Theory, Set Theory); 703.1 (Electric Networks); 921.5 (Optimization Techniques)
714 (Electronic Components & Tubes); 921 (Applied Mathematics); 703 (Electric Circuits); 721 (Computer Circuits & Logic Elements)
71 (ELECTRONICS & COMMUNICATION ENGINEERING); 92 (ENGINEERING MATHEMATICS); 70 (ELECTRICAL ENGINEERING, GENERAL); 72 (COMPUTERS & DATA PROCESSING)
Abstract: ...We propose C-tree, a two-level construction that first clusters sinks with common characteristics together, constructs low-level **Steiner trees** for each cluster, then performs a timing-driven Steiner construction on the top-level clustering...

16/5,K/15 (Item 5 from file: 8) <u>Links</u>
  Fulltext available through: <u>ScienceDirect</u>
Ei Compendex(R)
(c) 2007 Elsevier Eng. Info. Inc. All rights reserved.
08933797 **E.I. No:** EIP01456717510
Title: Efficient algorithms for the multicast trees under the packet-replication restrictions
Author: Chung, S.-J.; Hong, S.-P.; Chung, H.-S.
Corporate Source: Seoul National University, Seoul, South Korea
Source: IEICE Transactions on Communications v E84-B n 9 September 2001. p 2670-2680
Publication Year: 2001
CODEN: ITRCEC **ISSN:** 0916-8516
Language: English
Document Type: JA; (Journal Article) **Treatment:** A; (Applications); T; (Theoretical)
Journal Announcement: 0111W2
Abstract: In this paper, we are concerned in obtaining multicast trees in packet-switched networks such as ATM nets, when there exist constraints on the packet (cell)-replication capabilities of the individual switching nodes. This problem can be formulated as the Steiner tree problem with degree bounds on the nodes, so we call it the Degree-Constrained Steiner Tree problem (DCST). Four heuristic algorithms are proposed: the first is a combined version of two well-known Steiner tree algorithms, heuristic Naive and the shortest path heuristic (SPH), and the second is a relaxation algorithm based on a mathematical formulation of the DCST, and the last two use a tree reconfiguration scheme based on the concept of 'logical link.' We experimentally compare our algorithms with the previous ones in three respects; number of solved instances, objective value or tree cost, and computation time. The experimental results show that there are few instances unsolved by our algorithms, and the objective values are mostly within 5% of optimal. Computation times are also acceptable. 30 Refs.
Descriptors: *Multicasting; Algorithms; Packet networks; Constraint theory; Heuristic methods; Trees (mathematics); Problem solving
Identifiers: Multicast trees; Packet-replication restrictions; Relaxation algorithm
Classification Codes:
716.1 (Information & Communication Theory); 723.5 (Computer Applications); 721.1 (Computer Theory (Includes Formal Logic, Automata Theory, Switching Theory & Programming Theory)); 921.6 (Numerical Methods)
716 (Electronic Equipment, Radar, Radio & Television); 723 (Computer Software, Data Handling & Applications); 721 (Computer Circuits & Logic Elements); 921 (Applied Mathematics)
71 (ELECTRONICS & COMMUNICATION ENGINEERING); 72 (COMPUTERS & DATA PROCESSING); 92 (ENGINEERING MATHEMATICS)
Abstract: ...Degree-Constrained Steiner Tree problem (DCST). Four heuristic algorithms are proposed: the first is a combined version of two well-known **Steiner tree** algorithms, heuristic Naive and the shortest path heuristic (SPH), and the second is a relaxation....

16/5,K/16 (Item 6 from file: 8) <u>Links</u>
  Fulltext available through: <u>USPTO Full Text Retrieval Options</u>
Ei Compendex(R)
(c) 2007 Elsevier Eng. Info. Inc. All rights reserved.
08516143 **E.I. No:** EIP00035102781
Title: Associative-skew clock routing problem
Author: Chen, Yu; Kahng, Andrew B.; Qu, Gang; Zelikovsky, Alexander
Corporate Source: UCLA, Los Angeles, CA, USA
Conference Title: Proceedings of the 1999 IEEE/ACM International Conference on Computer-Aided Design (ICCAD-99)
Conference Location: San Jose, CA, USA **Conference Date:** 19991107-19991111
E.I. Conference No.: 56397
Source: IEEE/ACM International Conference on Computer-Aided Design, Digest of Technical Papers 1999. p 168-172
Publication Year: 1999
CODEN: DICDFD **ISSN:** 1092-3152
Language: English
Document Type: JA; (Journal Article) **Treatment:** A; (Applications); T; (Theoretical)
Journal Announcement: 0005W3

Abstract: We introduce the associative skew clock routing problem, which seeks a clock routing tree such that zero skew is preserved only within identified groups of sinks. The associative skew problem is easier to address within current EDA frameworks than useful-skew (skew-scheduling) approaches. and defines an interesting tradeoff between the traditional zero-skew clock routing problem (one sink group) and the Steiner minimum tree problem (n sink groups). We present a set of heuristic building blocks, including an efficient and optimal method of merging two zero-skew trees such that zero skew is preserved within the sink sets of each tree. Finally, we list a number open issues for research and practical application. (Author abstract) 21 Refs.
Descriptors: *Routers; Trees (mathematics); Set theory; Heuristic programming; Computer aided design; VLSI circuits; Topology; Algorithms
Identifiers: Associative skew clock routing; Rectilinear **Steiner** minimum tree; Zero skew tree; Deferred **merge** embedding; Bounded skew tree
  Classification Codes:
722.3 (Data Communication, Equipment & Techniques); 921.4 (Combinatorial Mathematics, Includes Graph Theory, Set Theory); 723.1 (Computer Programming); 723.5 (Computer Applications); 714.2 (Semiconductor Devices & Integrated Circuits)
722 (Computer Hardware); 921 (Applied Mathematics); 723 (Computer Software); 714 (Electronic Components)
72 (COMPUTERS & DATA PROCESSING); 92 (ENGINEERING MATHEMATICS); 71 (ELECTRONICS & COMMUNICATIONS)
Identifiers: Associative skew clock routing; Rectilinear **Steiner** minimum tree; Zero skew tree; Deferred **merge** embedding; Bounded skew tree

 16/5,K/17 (Item 7 from file: 8) <u>Links</u>
  Fulltext available through: <u>ScienceDirect</u>
Ei Compendex(R)
07868331 E.I. No: EIP97113926477
Title: DMRP: A distributed multicast routing protocol for ATM networks
Author: Venkateswaran, R.; Raghavendra, C.S.; Chen, X.; Kumar, V.P.
Corporate Source: Washington State Univ, Pullman, WA, USA
Conference Title: Proceedings of the 1997 IEEE ATM Workshop
Conference Location: Lisboa, Portugal **Conference Date:** 19970525-19970528
Sponsor: IEEE
E.I. Conference No.: 47249
Source: IEEE ATM Workshop, Proceedings 1997. IEEE, Piscataway, NJ, USA. p 263-271
Publication Year: 1997
CODEN: 002708
Language: English
Document Type: CA; (Conference Article) **Treatment:** A; (Applications); G; (General Review)
Journal Announcement: 9801W1
Abstract: In this paper, we present a Distributed Multicast Routing Protocol (DMRP) for dynamic computation of multicast trees. This protocol is a distributed version of a centralized heuristic for dynamic Steiner Tree computation. The protocol is deadlock-free and is a correct implementation of the centralized heuristic. It can be easily extended to the hierarchical framework supported by ATM Forum's PNNI protocols. This makes the protocol very scalable. Our motivation is to make this protocol a standard for multicasting under the PNNI framework. Our protocol draws a lot of inspiration from PIM, which has been proposed as the standard for multicasting in the internet domain. We would like to emphasize that unlike PIM which caters to maintaining only soft-states, DMRP maintains hard states. The hard states are required under the ATM framework and make the DMRP protocol compatible with the philosophy of PNNI. The sharing of the multicast tree among multiple senders makes effective use of the network resources. This reduces the overall cost of the multicast tree. The protocol relies on Participant Initiated Join, where the participant who wants to establish connection with the multicast group computes the path to the already existing multicast tree. Using simulations, we show that the number of messages generated before a participant can join the multicast tree is small. Further, the join latency is also small. The simplicity of the protocol lends itself to easy implementation for the support of multipoint connections under the PNNI framework. (Author abstract) 6 Refs.
Descriptors: *Asynchronous transfer mode; Network protocols; Congestion control (communication); Heuristic methods; Computer simulation; Trees (mathematics)
Identifiers: Distributed multicasting routing protocols (DMRP); **Steiner Tree** computation; Participant initiated **join**
  Classification Codes:
723.5 (Computer Applications); 921.4 (Combinatorial Mathematics, Includes Graph Theory, Set Theory)
716 (Radar, Radio & TV Electronic Equipment); 723 (Computer Software) ; 921 (Applied Mathematics)
71 (ELECTRONICS & COMMUNICATIONS); 72 (COMPUTERS & DATA PROCESSING); 92 (ENGINEERING MATHEMATICS)
Identifiers: Distributed multicasting routing protocols (DMRP); **Steiner Tree** computation; Participant initiated **join**

 16/5,K/18 (Item 8 from file: 8) <u>Links</u>
  Fulltext available through: <u>USPTO Full Text Retrieval Options</u>
Ei Compendex(R)
07800346 E.I. No: EIP97083784406
Title: Packing Steiner trees: Separation algorithms
Author: Grotschel, M.; Martin, A.; Weismantel, R.

Abstract: In this paper, we investigate separation problems for classes of inequalities valid for the polytope associated with the **Steiner tree packing** problem, a problem that arises, e.g., in very large-scale integration (VLSI) routing. The separation problem for Steiner partition inequalities is NP-hard in general. We show that it can be solved in polynomial time for those instances that come up in switchbox routing. Our algorithm uses dynamic programming techniques. These techniques are also applied to the much more complicated separation problem for alternating cycle inequalities. In this case, we can compute in polynomial time, given some point y, a lower bound for the gap x- a**T y over all alternating cycle inequalities a**T x greater than equivalent to alpha . This gives rise to a very effective separation heuristic. A by-product of our algorithm is the solution of a combinatorial optimization problem that is interesting in its own right: find a shortest path in a graph where the 'length' of a path is its usual length minus the length of its longest edge. 16 Ref.
Descriptors: *Algorithms; Dynamic programming
Identifiers: Polynomial time; Polytope; Steiner system; Graph path; Shortest path; Combinatorial optimization
  Classification Codes:
921.5 (Optimization Techniques)
921 (Applied Mathematics)
92 (ENGINEERING MATHEMATICS)
Title: Packing Steiner trees: Separation algorithms
Abstract: ...we investigate separation problems for classes of inequalities valid for the polytope associated with the Steiner tree packing problem, a problem that arises, e.g., in very large-scale integration (VLSI) routing. The...

16/5,K/19 (Item 9 from file: 8) **Links**
  Fulltext available through: SpringerLink   USPTO Full Text Retrieval Options
Ei Compendex(R)
07782101   E.I. No: EIP97083783920
Title: Steiner tree packing problem in VLSI design
Author: Groetschel, M.; Martin, A.; Weismantel, R.
Abstract: In this paper we describe several versions of the routing problem arising in VLSI design and indicate how the **Steiner tree packing** problem can be used to model these problems mathematically. We focus on switchbox muting problems and provide integer programming formulations for routing in the knock-knee and in the Manhattan model. We give a brief sketch of cutting plane algorithms that we developed and implemented for these two models. We report on computational experiments using standard test instances. Our codes are able to determine optimum solutions in most cases, and in particular, we can show that some of the instances have no feasible solution if Manhattan routing is used instead of knock-knee routing. (Author abstract) 20 Refs.
Descriptors: *Integer programming; VLSI circuits; Integrated circuit layout; Trees (mathematics); Mathematical models
Identifiers: Steiner tree packing; Switchbox routing; Manhattan model
  Classification Codes:
921.5 (Optimization Techniques); 714.2 (Semiconductor Devices & Integrated Circuits); 921.4 (Combinatorial Mathematics, Includes Graph Theory, Set Theory)
921 (Applied Mathematics); 714 (Electronic Components)
92 (ENGINEERING MATHEMATICS); 71 (ELECTRONICS & COMMUNICATIONS)
Title: Steiner tree packing problem in VLSI design
Abstract: ...describe several versions of the routing problem arising in VLSI design and indicate how the Steiner tree packing problem can be used to model these problems mathematically. We focus on switchbox muting problems...
Identifiers: Steiner tree packing; Switchbox routing; Manhattan model

16/5,K/20 (Item 10 from file: 8) **Links**
  Fulltext available through: ScienceDirect
Ei Compendex(R)
07364610   E.I. No: EIP96033109454
Title: Minimum-cost node-disjoint Steiner trees in series-parallel networks
Author: Chopra, Sunil; Talluri, Kalyan T.

CODEN: VLDEEZ
Language: English
Document Type: JA; (Journal Article) Treatment: T; (Theoretical)
Journal Announcement: 9605W3

Abstract: The routing problem in VLSI-layout can be modeled as a problem of packing node-disjoint Steiner trees in a graph. The problem is as follows: Given an undirected network G equals (V,E) and a net list Psi equals left brace N//i, i equals 1,..., r right brace , a family Gamma //G equals left brace T//N//((//i//) equals (V//N//((//i//), E//N//((//i//)), i equals 1,..., r right brace is a node-disjoint family of Steiner trees spanning Psi if T//N//((//i//) is a Steiner tree spanning N//i for i equals 1,..., r and V//N//((//i//) qq V//N//((//j//) equals for i does not equal j. The edge-disjoint version of this problem is known to be NP-hard for series-parallel graphs (see Richey and Parker left bracket 5 right bracket). In this paper we give a O(n**5) algorithm for finding a minimum-cost node-disjoint family of Steiner trees in series-parallel networks. Our algorithm can be extended to k-trees and is polynomial for fixed k. (Author abstract) 6 Refs.
Descriptors: *Integrated circuit layout; Trees (mathematics); Mathematical models; Computational complexity; Algorithms; Polynomials
Identifiers: Steiner trees; Series parallel graphs; Routing problem
  Classification Codes:
714.2 (Semiconductor Devices & Integrated Circuits); 921.4 (Combinatorial Mathematics, Includes Graph Theory, Set Theory); 721.1 (Computer Theory, Includes Formal Logic, Automata Theory, Switching Theory, Programming Theory); 921.1 (Algebra)
714 (Electronic Components); 921 (Applied Mathematics); 721 (Computer Circuits & Logic Elements)
71 (ELECTRONICS & COMMUNICATIONS); 92 (ENGINEERING MATHEMATICS); 72 (COMPUTERS & DATA PROCESSING)
Abstract: The routing problem in VLSI-layout can be modeled as a problem of packing node-disjoint Steiner trees in a graph. The problem is as follows: Given an undirected network G equals (V...

16/5,K/21 (Item 11 from file: 8) Links
  Fulltext available through: ScienceDirect
Ei Compendex(R)
05905255 E.I. Monthly No: EIM9005-021516
Title: Automatic generation of symbolic cells from a net-list description.
Author: Costa, Raffaele; Curatelli, Francesco; Caviglia, Daniele D.; Bisio, Giacomo M.
Corporate Source: DIBE, Univ of Genova, Genoa, Italy
Conference Title: COMPEURO '89 - 3rd Annual European Computer Conference
Conference Location: Hamburg, West Ger Conference Date: 19890508
Sponsor: IEEE, Computer Soc, Los Alamitos, CA, USA; Gesellschaft fuer Informatik, West Ger; Verband Deutscher Elektrotechniker, Frankfurt am Main, West Ger
E.I. Conference No.: 12818
Source: VLSI and Computer Peripherals. Publ by IEEE, IEEE Service Center, Piscataway, NJ, USA. Available from IEEE Service Cent (cat n 89CH2704-5), Piscataway, NJ, USA. p 5/35-39
Publication Year: 1989
  ISBN: 0-8186-1940-6
Language: English
Document Type: PA; (Conference Paper) Treatment: A; (Applications)
Journal Announcement: 9005

Abstract: A tool capable of synthesizing the symbolic layout of a CMOS cell from its circuit descriptions is presented. The synthesis process is guided by topological constraints on pin and transistor positions, maximum lengths of poly and diffusion wires, and the specification of a preferred layer for each electrical node. The optimization criteria take into account cell area and aspect ratio, wire length, capacitance to the substrate, and contact and via minimization. The novel placement strategy includes transistor clustering into regions, global region placement by linear ordering, and two-dimensional local transistor placement. The routing combines Steiner trees and Lee algorithms. The program is fast and has been thoroughly tested on small and medium-sized cells. 13 Refs.
Descriptors: *INTEGRATED CIRCUITS, VLSI--*Layout; SEMICONDUCTOR DEVICES, MOS; TRANSISTORS; COMPUTER PROGRAMMING--Algorithms
Identifiers: CMOS CELLS; NETLIST DISPLAYS; STEINER TREES; LEE ALGORITHMS
  Classification Codes:
713 (Electronic Circuits); 714 (Electronic Components); 723 (Computer Software)
71 (ELECTRONICS & COMMUNICATIONS); 72 (COMPUTERS & DATA PROCESSING)
Abstract: ...regions, global region placement by linear ordering, and two-dimensional local transistor placement. The routing combines Steiner trees and Lee algorithms. The program is fast and has been thoroughly tested on small and...

16/5,K/22 (Item 1 from file: 65) Links
  Fulltext available through: ScienceDirect
Inside Conferences
01224966 Inside Conference Item ID: CN012026110
Two Steiner Tree Packing Problems
  Pulleyblank, W. R.
Conference: Theory of computing - 27th Annual symposium
  ANNUAL ACM SYMPOSIUM ON THEORY OF COMPUTING , 1995; VOL 27 P: 383-387

ACM Press, 1995
ISSN: 0737-8017 ISBN: 0897917189
Language: English Document Type: Conference Papers
Sponsor: Association for Computing Machinery
Location: Las Vegas, NV
Date: May 1995 (199505) (199505)
British Library Item Location: 1073.870000
Descriptors: computing; ACM
Two Steiner Tree Packing Problems

16/5,K/23 (Item 2 from file: 65) Links
Fulltext available through: ScienceDirect
Inside Conferences
(c) 2007 BLDSC all rts. reserv. All rights reserved.
00737620 Inside Conference Item ID: CN007195930
Steiner Trees and Packing Constants in Graph-Metric Spaces
Prass, P.
Conference: Graphs and combinatorial optimization - 3rd Workshop
PB REPORTS , PB94-110947 P: 24-26
[np], [nd]
Language: English Document Type: Conference Papers and programme
Sponsor: United States Department of Commerce
Location: Enschede, The Netherlands
Date: Jun 1993 (199306) (199306)
British Library Item Location: 6413.350000F
Note:
3; microfiche
Descriptors: graphs; combinatorial optimization; USDOC
Steiner Trees and Packing Constants in Graph-Metric Spaces

16/5,K/24 (Item 1 from file: 2) Links
Fulltext available through: John Wiley and Sons USPTO Full Text Retrieval Options
INSPEC
(c) 2007 Institution of Electrical Engineers. All rights reserved.
08430399 INSPEC Abstract Number: B2002-12-2570A-018
Title: A branch-and-price algorithm for switch-box routing
Author Jorgensen, D.G.; Meyling, M.
Author Affiliation: Dept. of Comput. Sci., Copenhagen Univ., Denmark
Journal: Networks   vol.40, no.1   p. 13-26
Publisher: Wiley ,
Publication Date: Aug. 2002 Country of Publication: USA
CODEN: NTWKAA ISSN: 0028-3045
SICI: 0028-3045(200208)40:1L.13:BPAS;1-X
Material Identity Number: N073-2002-005
Item Identifier (DOI): 10.1002/net.10029
Language: English   Document Type: Journal Paper (JP)
Treatment: Practical (P); Theoretical (T)
Abstract: Routing in VLSI design concerns the wiring of a chip after the logical modules have been placed. A subproblem
occurring in VLSI design is switch-box routing. Switch-box routing can be formulated as the problem of packing Steiner
trees in a grid graph. The only previous exact solution method for switch-box routing uses a branch-and-cut approach.
The aim of this work is to solve the switch-box routing problem to optimality by using a branch-and-price algorithm based
on an IP model where variables represent Steiner trees and where the pricing problem becomes the problem of finding a
Steiner tree in a graph. In the primal algorithm, the focal points are branching strategy, pricing strategy, perturbation of the
linear program, and computation of lower bounds to terminate column generation early. The final implementation yields
optimal solutions in the knock-knee model to seven classic switch-box instances, of which three had not been solved to
optimality prior to this work. (18 Refs)
Subfile: B
Descriptors: integrated circuit layout; network routing; optimisation; trees (mathematics); VLSI
Identifiers: branch-and-price algorithm; switch-box routing; VLSI design; chip wiring; Steiner trees; grid graph; branching
strategy; pricing strategy; linear program perturbation; column generation termination; knock-knee model; optimization
Class Codes: B2570A (Semiconductor integrated circuit design, layout, modelling and testing); B0250 (Combinatorial
mathematics); B1110 (Network topology)
Copyright 2002, IEE
Abstract: ...design is switch-box routing. Switch-box routing can be formulated as the problem of packing Steiner trees
in a grid graph. The only previous exact solution method for switch-box routing uses...

16/5,K/25 (Item 2 from file: 2) Links
Fulltext available through: USPTO Full Text Retrieval Options
INSPEC
(c) 2007 Institution of Electrical Engineers. All rights reserved.

08185265   INSPEC Abstract Number: B2002-03-0260-059, C2002-03-1180-071
Title: A branch-and-price algorithm for the Steiner tree packing problem
Author Gue-woong Jeong; Kyungsik Lee; Sungsoo Park; Kyungchul Park
Author Affiliation: Dept. of Ind. Eng., Korea Adv. Inst. of Sci. & Technol., Seoul, South Korea
Journal: Computers & Operations Research   vol.29, no.3   p. 221-41
Publisher: Elsevier ,
Publication Date: March 2002 Country of Publication: UK
CODEN: CMORAP ISSN: 0305-0548
SICI: 0305-0548(200203)29:3L.221:BPAS;1-0
   Material Identity Number: C175-2002-002
U.S. Copyright Clearance Center Code: 0305-0548/02/$20.00
Document Number: S0305-0548(00)00066-6
Language: English   Document Type: Journal Paper (JP)
Treatment: Theoretical (T)

Abstract: The paper, deals with the **Steiner tree packing** problem. For a given undirected graph G=(V,E) with positive integer capacities and nonnegative weights on its edges, and a list of node sets (nets), the problem is to find a connection of nets which satisfies the edge capacity limits and minimizes the total weights. We focus on the switchbox routing problem in knock-knee model and formulate this problem as an integer programming problem using Steiner tree variables. We-develop a branch-and-price algorithm. The algorithm is applied on some standard test instances and we compare the performances with the results using a cutting plane approach. Computational results show that our algorithm is competitive with the cutting plane algorithm presented by M. Grotschel et al. (1996) and can be used to solve practically sized problems. (23 Refs)
   Subfile: B C
Descriptors: bin packing; graph theory; integer programming; network routing; tree searching
Identifiers: branch-and-price algorithm; **Steiner tree packing** problem; undirected graph; positive integer capacities; nonnegative weights ; node sets; edge capacity limits; total weight minimization; switchbox routing problem; knock-knee model; integer programming; Steiner tree variables; standard test instances; cutting plane approach; STP; column generation
Class Codes: B0260 (Optimisation techniques); B0250 (Combinatorial mathematics); B1130 (General circuit analysis and synthesis methods); C1180 (Optimisation techniques); C1160 (Combinatorial mathematics); C4240 (Programming and algorithm theory); C6120 (File organisation)
   Copyright 2002, IEE
Title: A branch-and-price algorithm for the Steiner tree packing problem
Abstract: The paper, deals with the Steiner tree packing problem. For a given undirected graph G=(V,E) with positive integer capacities and nonnegative...
Identifiers: ...Steiner tree packing problem

16/5,K/26 (Item 3 from file: 2) Links
   Fulltext available through: ScienceDirect
INSPEC
08183959   INSPEC Abstract Number: C2002-03-4260-048
Title: Connected joins in graphs
Author Sebo, A.; Tannier, E.
Author Affiliation: Lab. Leibniz, IMAG, Grenoble, France
Conference Title: Integer Programming and Combinatorial Optimization. 8th International IPCO Conference. Proceedings (Lecture Notes in Computer Science Vol.2081)   p. 383-95
Editor(s): Aardal, K.; Gerards, B.
Publisher: Springer-Verlag , Berlin, Germany
Publication Date: 2001 Country of Publication: Germany xi+421 pp.
ISBN: 3 540 42225 0   Material Identity Number: XX-2001-02092
Conference Title: Integer Programming and Combinatorial Optimization. 8th International IPCO Conference. Proceedings
Conference Date: 13-15 June 2001   Conference Location: Utrecht, Netherlands
Language: English   Document Type: Conference Paper (PA)
Treatment: Practical (P); Theoretical (T)

Abstract: A join in a graph is a set F of edges such that for every circuit C, ; C intersection F; <or= ; C F; . We study the problem of finding a connected join covering a given subset of vertices of the graph, that is a **Steiner tree** which is a **join** at the same time. This turns out to contain the question of finding a T-join of minimum cardinality (or weight) which is, in addition, connected. This last problem is mentioned to be open in a survey of A. Frank (1996), and is motivated by its link to integral packings of T-cuts: if a minimum T-join F is connected, then there exists an integral packing of T-cuts of cardinality ; F; . The problems we deal with are closely related to some known NP-complete problems: deciding the existence of a connected T-join; finding the minimum cardinality of a connected T-join; the **Steiner tree** problem; subgraph isomorphism. We also explore some of these connections. (20 Refs)
   Subfile: C
Descriptors: computational complexity; computational geometry; graph theory
Identifiers: connected joins; graphs; vertices; Steiner tree; minimum cardinality; integral packing; NP-complete problems; Steiner tree problem; subgraph isomorphism
Class Codes: C4260 (Computational geometry); C4240C (Computational complexity); C1160 (Combinatorial mathematics)

Abstract: ...a connected join covering a given subset of vertices of the graph, that is a **Steiner tree** which is a **join** at the same time. This turns out to contain the question of finding a T... ...the existence of a connected T-join; finding the minimum cardinality of a connected T-**join**; the **Steiner tree** problem; subgraph isomorphism. We also explore some of these connections.

16/5,K/27 (Item 4 from file: 2) <u>Links</u>
   Fulltext available through: <u>USPTO Full Text Retrieval Options</u>
INSPEC

08163198 INSPEC Abstract Number: B2002-03-1110-001
Title: Buffered Steiner trees for difficult instances
Author Alpert, C.J.; Gandham, G.; Hrkic, M.; Jiang Hu; Kahng, A.B.; Lillis, J.; Bao Liu; Quay, S.T.; Sapatnekar, S.S.; Sullivan, A.J.
Author Affiliation: IBM Corp., Austin, TX, USA
Journal: IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems **Conference Title:** IEEE Trans. Comput.-Aided Des. Integr. Circuits Syst. (USA)   vol.21, no.1   p. 3-14
Publisher: IEEE ,
Publication Date: Jan. 2002 **Country of Publication:** USA
CODEN: ITCSDI ISSN: 0278-0070
SICI: 0278-0070(200201)21:1L.3:BSTD;1-1
   Material Identity Number: B959-2002-001
U.S. Copyright Clearance Center Code: 0278-0070/02/$17.00
Conference Title: International Symposium on Physical Design (ISPD)
Conference Date: 2001   **Conference Location:** Sonoma, CA, USA
Document Number: S0278-0070(02)00092-1
Language: English   **Document Type:** Conference Paper (PA); Journal Paper (JP)
Treatment: Theoretical (T)

Abstract: With the rapid scaling of integrated-circuit technology, buffer insertion has become an increasingly critical optimization technique in high-performance design. The problem of finding a buffered Steiner tree with optimal delay characteristics has been an active area of research and excellent solutions exist for most instances. However, there exists a class of real "difficult" instances, which are characterized by a large number of sinks (e.g., 20-100), large variations in sink criticalities, nonuniform sink distribution, and varying polarity requirements. Existing techniques are either inefficient, wasteful of buffering resources, or unable to find a high-quality solution. We propose C-tree, a two-level construction that first clusters sinks with common characteristics **together**, constructs low-level **Steiner trees** for each cluster, then performs a timing-driven Steiner construction on the top-level clustering. We show that this hierarchical approach can achieve higher quality solutions with fewer resources compared to traditional timing-driven Steiner trees. (23 Refs)

 Subfile: B
Descriptors: buffer circuits; circuit optimisation; integrated circuit design; trees (mathematics)
Identifiers: buffered Steiner tree; integrated circuit design; clustering algorithm; buffer insertion; optimization; delay characteristics; sink distribution; C-tree
Class Codes: B1110 (Network topology); B2570A (Semiconductor integrated circuit design, layout, modelling and testing); B0260 (Optimisation techniques); B0250 (Combinatorial mathematics)

Abstract: ...We propose C-tree, a two-level construction that first clusters sinks with common characteristics **together**, constructs low-level **Steiner trees** for each cluster, then performs a timing-driven Steiner construction on the top-level clustering...

 16/5,K/28 (Item 5 from file: 2) <u>Links</u>
   Fulltext available through: <u>USPTO Full Text Retrieval Options</u>
INSPEC

08067450   INSPEC Abstract Number: B2001-11-6150C-043
Title: Efficient algorithms for the multicast trees under the packet-replication restrictions
Author Sung-Jin Chung; Sung-Pil Hong; Hoo-Sang Chung
Author Affiliation: Seoul Nat. Univ., South Korea
Journal: IEICE Transactions on Communications   vol.E84-B, no.9   p. 2670-80
Publisher: Inst. Electron. Inf. & Commun. Eng ,
Publication Date: Sept. 2001 **Country of Publication:** Japan
CODEN: ITCMEZ ISSN: 0916-8516
SICI: 0916-8516(200109)E84B:9L.2670:EAMT;1-E
   Material Identity Number: P711-2001-009
Language: English   **Document Type:** Journal Paper (JP)
Treatment: Theoretical (T); Experimental (X)

Abstract: We are concerned with obtaining multicast trees in packet-switched networks such as ATM networks, when there exist constraints on the packet (cell)-replication capabilities of the individual switching nodes. This problem can be formulated as the Steiner tree problem with degree bounds on the nodes, so we call it the degree-constrained Steiner tree problem (DCST). Four heuristic algorithms are proposed: the first is a **combined** version of two well-known **Steiner tree** algorithms, heuristic naive and the shortest path heuristic (SPH), and the second is a relaxation algorithm based on a mathematical formulation of the DCST, and the last two use a tree reconfiguration scheme based on the concept of

'logical link'. We experimentally compare our algorithms with the previous ones in three respects: number of solved instances, objective value or tree cost, and computation time. The experimental results show that there are few instances unsolved by our algorithms, and the objective values are mostly within 5% of optimal. Computation times are also acceptable. (30 Refs)

Subfile: B

Descriptors: asynchronous transfer mode; multicast communication; network topology; packet switching; telecommunication network routing; trees (mathematics)

Identifiers: multicast trees; packet-replication restrictions; packet-switched networks; ATM networks; cell replication; degree-constrained Steiner tree problem; heuristic naive algorithm; shortest path heuristic algorithm; relaxation algorithm; tree reconfiguration; logical link; tree cost; computation time; solved instances

Class Codes: B6150C (Communication switching); B0250 (Combinatorial mathematics); B6150P (Communication network design, planning and routing)

Copyright 2001, IEE

Abstract: ...degree-constrained Steiner tree problem (DCST). Four heuristic algorithms are proposed: the first is a combined version of two well-known **Steiner tree** algorithms, heuristic naive and the shortest path heuristic (SPH), and the second is a relaxation...

16/5,K/29 (Item 6 from file: 2) <u>Links</u>

Fulltext available through: <u>ScienceDirect</u>

INSPEC

07467923   INSPEC Abstract Number: B2000-02-0250-054, C2000-02-1160-069

Title: Vertex-disjoint packing of two Steiner trees: polyhedra and branch-and-cut

Author Uchoa, E.; Poggi de Aragao, M.

Author Affiliation: Dept. de Inf., Pontificia Univ. Catolica do Rio de Janeiro, Brazil

Conference Title: Integer Programming and Combinatorial Optimization. 7th International IPCO Conference. Proceedings   p. 439-52

Editor(s): Cornuejols, G.; Burkard, R.E.; Woeginger, G.J.

Publisher: Springer-Verlag , Berlin, Germany

Publication Date: 1999 **Country of Publication:** Germany ix+452 pp.

ISBN: 3 540 66019 4   **Material Identity Number:** XX-1999-01984

Conference Title: Integer Programming and Combinatorial Optimization. 7th International IPCO Conference. Proceedings

Conference Date: 9-11 June 1999   **Conference Location:** Graz, Austria

Language: English   **Document Type:** Conference Paper (PA)

Treatment: Theoretical (T)

Abstract: Consider the problem of routing the electrical connections among two large terminal sets in circuit layout. A realistic model for this problem is given by the vertex-disjoint **packing** of two **Steiner trees** (2VPST), which is known to be NP-complete. This work presents an investigation on the 2VPST polyhedra. The main idea is to depart from facet-defining inequalities for a vertex-weighted Steiner tree polyhedra. Some of these inequalities are proven to also define facets for the packing polyhedra, while others are lifted to derive new important families of inequalities, including proven facets. Separation algorithms are also presented. The resulting branch-and-cut code has an excellent performance and is capable of solving problems on grid graphs with up to 10000 vertices and 5000 terminals in a few minutes. (8 Refs)

Subfile: B C

Descriptors: circuit layout; trees (mathematics)

Identifiers: Steiner trees; polyhedra; branch-and-cut; vertex-disjoint packing; NP-complete; Steiner tree polyhedra; packing polyhedra

Class Codes: B0250 (Combinatorial mathematics); B1110 (Network topology); C1160 (Combinatorial mathematics)

Copyright 2000, IEE

Title: Vertex-disjoint packing of two Steiner trees: polyhedra and branch-and-cut

Abstract: ...in circuit layout. A realistic model for this problem is given by the vertex-disjoint packing of two Steiner trees (2VPST), which is known to be NP-complete. This work presents an investigation on the...

16/5,K/30 (Item 7 from file: 2) <u>Links</u>

Fulltext available through: <u>USPTO Full Text Retrieval Options</u>

INSPEC

05797132   INSPEC Abstract Number: B9412-0250-004, C9412-1290-005

Title: Comparison of formulations and a heuristic for packing Steiner trees in a graph

Author Chopra, S.

Author Affiliation: J.L. Kellogg Graduate Sch. of Manage., Northwestern Univ., Evanston, IL, USA

Journal: Annals of Operations Research   vol.50   p. 143-71

Publication Date: Sept. 1994 **Country of Publication:** Switzerland

CODEN: AOREEV **ISSN:** 0254-5330

Language: English   **Document Type:** Journal Paper (JP)

Treatment: Applications (A); Theoretical (T)

Abstract: In this paper, we consider the problem of **packing Steiner trees** in a graph. This problem arises during the global routing phase of circuit layout design. We consider various integer programming formulations and rank them according to lower bounds they provide as linear programming (LP) relaxations. We discuss a solution procedure to obtain both lower and upper bounds using one of the LP-relaxations. Computational results to test the effectiveness of our

procedures are provided. (19 Refs)
Subfile: B C
Descriptors: circuit layout; integer programming; linear programming; network routing; operations research; relaxation theory; trees (mathematics)
Identifiers: Steiner trees; packing problem; heuristic; graph theory; global routing; circuit layout design; integer programming; lower bounds; linear programming relaxations; upper bounds
Class Codes: B0250 (Combinatorial mathematics); B0260 (Optimisation techniques); B1130 (General analysis and synthesis methods); C1290 (Applications of systems theory); C1160 (Combinatorial mathematics); C1180 (Optimisation techniques)
Title: Comparison of formulations and a heuristic for packing Steiner trees in a graph
Abstract: In this paper, we consider the problem of packing Steiner trees in a graph. This problem arises during the global routing phase of circuit layout design...

16/5,K/31 (Item 1 from file: 6) Links
Fulltext available through: Check for PDF Download Availability and Purchase
NTIS

Twente Workshop on Graphs and Combinatorial Optimization (3rd). Held in Enschede on June 2-4, 1993.
Scientific Program
(Memorandum rept)
Faigle, U. ; Hoede, C.
Technische Univ. Twente, Enschede (Netherlands). Faculty of Applied Mathematics.
Corporate Source Codes: 090700007
Report Number: MEMO-1132
May 93   242p
Language: English   Document Type: Conference proceeding
Journal Announcement: GRAI9403
See also PB94-110954, N92-24905 and PB93-195568.
Order this product from NTIS by: phone at 1-800-553-NTIS (U.S. customers); (703)605-6000 (other countries); fax at (703)321-8547; and email at orders@ntis.fedworld.gov. NTIS is located at 5285 Port Royal Road, Springfield, VA, 22161, USA.
NTIS Prices: PC A11/MF A03
Country of Publication: Netherlands
Partial contents: Almost Distance-Hereditary Graphs; Toughness and Triangle-Free Graphs; Applications of an Algebraic Monge Property; On Special Antimagic Labelings; A Linear Time Algorithm for Finding Tree-Decompositions of Small Treewidth; Cycle Lengths in Non-Bipartite Graphs; **Steiner Trees** and **Packing** Constants in Graph-Metric Spaces; Ordered Matroids and Regular Independence Systems; Generalized Strongly Chordal Graphs; Nordhaus-Gaddum Type Inequalities for the Average Distance of a Graph; Determination of the Rank of Lefschetz Matrices of Products of Posets; Linear Programming in Random Polynomial Time; Polymatroids of the Cone of Boolean Submodular Functions; Bipartite Regular Graphs with Large Diameters.
Descriptors: *Graph theory; *Meetings; Problem solving; Linear programming; Game theory; Scheduling; Matrices; Abstracts; Theorems
Identifiers: *Foreign technology; Combinatorial optimization; Graph coloring; Matroids; NTISTFNPO
Section Headings: 72B (Mathematical Sciences--Algebra, Analysis, Geometry, and Mathematical Logic); 72E (Mathematical Sciences--Operations Research)
...Time Algorithm for Finding Tree-Decompositions of Small Treewidth; Cycle Lengths in Non-Bipartite Graphs; **Steiner Trees** and **Packing** Constants in Graph-Metric Spaces; Ordered Matroids and Regular Independence Systems; Generalized Strongly Chordal Graphs...

16/5,K/32 (Item 2 from file: 6) Links
Fulltext available through: Check for PDF Download Availability and Purchase
NTIS

Packen von Steinerbaeumen: Polyedrische Studien und Anwendung (Packing of Steiner Trees: Polyhedric Studies and Application)
(Ph.D. Thesis)
Martin, A.
Technische Univ. Berlin (Germany, F.R.). Fachgebiet Raumfahrt.
Corporate Source Codes: 030172081; TJ477159
Report Number: ETN-93-93796
1992   196p
Language: German   Document Type: Thesis
Journal Announcement: GRAI9321; STAR3111
Text in German.
Order this product from NTIS by: phone at 1-800-553-NTIS (U.S. customers); (703)605-6000 (other countries); fax at (703)321-8547; and email at orders@ntis.fedworld.gov. NTIS is located at 5285 Port Royal Road, Springfield, VA, 22161, USA.
NTIS Prices: PC A09/MF A03
Country of Publication: Germany
A formulation to solve the **Steiner tree packing** problem, by means of graph theory, linear algebra polyhedra theory, and

linear programming is developed. The connectivity problem in very large scale integration design, and plane, Manhattan, and knock knee models are presented. Some algorithms for switch box connectivity, such as multicommodity flows in graphs are proposed. Canonic, facet based, and explicit formulation of arborescence polyhedra were examined. The chosen polyhedron was defined as the convex hull of all incidence vectors of Steiner tree packings of a given instance of the problem. A cutting plane algorithm to solve inequalities for polyhedron facet definition with a branch and cut process was developed. Partitioning procedures were realized to solve the separation problem inequalities. The method was applied to problems for the literature.

Descriptors: *Graph theory; *Integrated circuits; *Linear programming; *Optimization; *Packaging; *Trees (Mathematics); Combinatorial analysis; Constraints; Graphs (Charts); Heuristic methods; Homotopy theory; Problem solving; Set theory; Simplex method; Topology

Identifiers: *Foreign technology; Theses; NTISNASAE

Section Headings: 72E (Mathematical Sciences--Operations Research)

Packen von Steinerbaeumen: Polyedrische Studien und Anwendung (Packing of Steiner Trees: Polyhedric Studies and Application)

A formulation to solve the Steiner tree packing problem, by means of graph theory, linear algebra polyhedra theory, and linear programming is developed...

16/5,K/33 (Item 1 from file: 144) <u>Links</u>
  Fulltext available through: <u>USPTO Full Text Retrieval Options</u>
Pascal

  16491488   PASCAL No.: 04-0136014
  Effective location-guided tree construction algorithms for small group
multicast in MANET
  IEEE Infocom 2002 : New York NY, 23-27 June 2002
  KAI CHEN; NAHRSTEDT Klara
  Computer Science Department, University of Illinois at Urbana-Champaign,
Urbana, IL 61801, United States
  Conference on computer communicationsIEEE Communications Society. Annual
Conference, 21IEEE Computer Society. Annual Conference, 21 (USA)
2002-06-23
  Journal: Proceedings - IEEE Infocom,
2002 1180-1189
  ISBN: 0-7803-7476-2 ISSN: 0743-166X Availability: INIST-Y
37882; 354000117749251250
  No. of Refs.: 24 ref.
  Document Type: P (Serial); C (Conference Proceedings) ; A (Analytic)
  Country of Publication: United States
  Language: English
  Group communication has become increasingly important in mobile ad hoc
networks (MANET). Current multicast routing protocols in MANET have been
shown to have large overhead due to dynamic network topology. To overcome
this problem, there is a recent shift towards stateless multicast in small
groups (DDM (1)). DDM queries the underlying unicast routing protocol to
forward data packets towards members of a multicast group. The multicast
distribution tree in DDM is implicit and cannot be controlled by the upper
transport and application layers. In this paper, we introduce another small
group multicast scheme, based on packet encapsulation, which uses novel
packet distribution tree construction algorithms for efficient data
delivery. The packet distribution tree is constructed explicitly with the
goal of minimizing .the overall bandwidth cost of the tree. The tree
construction algorithms include a location-guided k-ary (LGK) tree and a
location-guided Steiner (LGS) tree. Both of them utilize the geometric
locations of the destination nodes as heuristics to compute the trees, and
are accompanied by a hybrid location update mechanism to disseminate
location information among a group of nodes. Our simulation results show
that LGS tree has lower bandwidth cost than LGK tree when the location
information of the nodes is up-to-date, and its cost is similar to that of .
an optimal Steiner multicast tree. When location information of the nodes
is out-dated, LGK tree outperforms LGS tree due to its lower computational
complexity.
  English Descriptors: Localization; Tree algorithm; Multicast; Mobile
  radiocommunication; Ad hoc network; Wireless telecommunication;
  Transmission protocol; Multicast protocols; Routing protocols; Network
  architecture; Topological structure; **Packet** switching; Algorithm
  performance; **Steiner tree** problem; Heuristic method;
  Simulation; Performance evaluation; Computational complexity; Data
  broadcast
French Descriptors: Localisation; Algorithme en arbre; Multidestinataire;

Radiocommunication service mobile; Reseau ad hoc; Telecommunication sans
fil; Protocole transmission; Protocole multidestinataire; Protocole
routage; Architecture reseau; Structure topologique; Commutation paquet;
Performance algorithme; Probleme arbre Steiner; Methode heuristique;
Simulation; Evaluation performance; Complexite calcul; Diffusion donnee
Classification Codes: 001D04B04G2; 001D04B03A; 001D04B02D; 001D04B02F

...English Descriptors: Ad hoc network; Wireless telecommunication;
Transmission protocol; Multicast protocols; Routing protocols; Network
architecture; Topological structure; **Packet** switching; Algorithm
performance; **Steiner tree** problem; Heuristic method;
Simulation; Performance evaluation; Computational complexity; Data
broadcast

16/5,K/34 (Item 2 from file: 144) <u>Links</u>
Fulltext available through: <u>ScienceDirect</u>
Pascal

15523738   PASCAL No.: 02-0221029
Multicast routing with bandwidth requirement in the case of incomplete
information as a Steiner tree problem
Routage multicast avec information incomplete sur la bande passante vu
comme un probleme de Steiner
LEGUESDRON Patrice; LEVENDOVSZKY Janos; MOLNAR Miklos; VEGSO Csaba
CNRS. Institut de recherche en informatique et systemes aleatoires,
Rennes, France; Universite de Rennes 1. Institut de recherche en
informatique et systemes aleatoires, Rennes, France; Institut national des
sciences appliquees de Rennes. Institut de recherche en informatique et
systemes aleatoires, Rennes, France; Institut national de recherche en
informatique et en automatique. Institut de recherche en informatique et
systemes aleatoires, Rennes, France
Dans cet article, nous developpons un nouvel algorithme pour le routage
multicast dans les reseaux de communication. Nous transformons le probleme
du routage multicast avec contrainte de bande passante lorsque
l'information est incomplete en un probleme de Steiner deterministe. Les
algorithmes de la methode "tabou" sont ensuite utilises pour s'assurer de
la bonne qualite des solutions sous optimales du routage multicast en un
temps polynomial.
English Descriptors: Routing algorithm; Network routing; Telecommunication
network; Multicast; Incomplete information; Deterministic approach;
Steiner tree problem; Tabu search; **Packet** switching;
Maximum likelihood; Polynomial time; Network architecture; Service
quality
French Descriptors: Algorithme routage; Routage reseau; Reseau
telecommunication; Multidestinataire; Information incomplete; Approche
deterministe; Probleme arbre Steiner; Recherche tabou; Commutation paquet
; Maximum vraisemblance; Temps polynomial; Architecture reseau; Qualite
service
Classification Codes: 001D04B02D

English Descriptors: Routing algorithm; Network routing; Telecommunication
network; Multicast; Incomplete information; Deterministic approach;
Steiner tree problem; Tabu search; **Packet** switching;
Maximum likelihood; Polynomial time; Network architecture; Service

quality

16/5,K/35 (Item 3 from file: 144) <u>Links</u>
 Fulltext available through: <u>USPTO Full Text Retrieval Options</u>
Pascal
(c) 2007 INIST/CNRS. All rights reserved.

 14644997 PASCAL No.: 00-0316510
 Rank inequalities for packing designs and sparse triple systems
 LATIN 2000 : theoretical informatics : Punta del Este, 10-14 April 2000
 MOURA L
 GONNET Gaston H, ed; PANARIO Daniel, ed; VIOLA Alfredo, ed
 Department of Computer Science, University of Toronto, and The Fields
Institute for Research in Mathematical Sciences, Canada
 Latin American symposium on theoretical informatics, 4 (Punta del Este
URY) 2000-04-10
 Journal: Lecture notes in computer science,
2000, 1776 105-114
 ISBN: 3-540-67306-7 ISSN: 0302-9743 Availability:
INIST-16343; 354000080064480110
 No. of Refs.: 21 ref.
 Document Type: P (Serial); C (Conference Proceedings) ; A (Analytic)
 Country of Publication: Germany
 Language: English

Combinatorial designs find numerous applications in computer science, and
are closely related to problems in coding theory. Packing designs
correspond to codes with constant weight; 4-sparse partial Steiner triple
systems (4-sparse PSTSs) correspond to erasure-resilient codes able to
correct all (except for "bad ones") 4-erasures, which are useful in
handling failures in large disk arrays (4,10). The study of polytopes
associated with combinatorial problems has proven to be important for both
algorithms and theory. However, research on polytopes for problems in
combinatorial design and coding theories have been pursued only recently
(14,15,17,20,21). In this article, polytopes associated with t-(v, k, A)
packing designs and sparse PSTSs are studied. The subpacking and sparseness
inequalities are introduced. These can be regarded as rank inequalities for
the independence systems associated with these designs. Conditions under
which subpacking inequalities define facets are studied. Sparseness
inequalities are proven to induce facets for the sparse PSTS polytope; some
extremal families of PSTS known as Erdoes configurations play a central .
role in this proof. The incorporation of these inequalities in polyhedral
algorithms and their use for deriving upper bounds on the packing numbers
are suggested. A sample of 4-sparse PSTS(v), v <= 16, obtained by such
an algorithm is shown; an upper bound on the size of m-sparse PSTSs is
presented.
English Descriptors: Computer theory; Combinatorial problem; **Steiner**
 tree problem; Bin **packing** problem; Polytope
French Descriptors: Informatique theorique; Probleme combinatoire; Probleme
 arbre Steiner; Probleme remplissage; Polytope
Classification Codes: 001D02A06

English Descriptors: Computer theory; Combinatorial problem; **Steiner**
 tree problem; Bin **packing** problem; Polytope

16/5,K/36 (Item 4 from file: 144) <u>Links</u>
 Fulltext available through: <u>USPTO Full Text Retrieval Options</u>
Pascal
(c) 2007 INIST/CNRS. All rights reserved.

 14228689 PASCAL No.: 99-0430150
 A polyhedral algorithm for packings and designs
 Algorithms : Prague, 16-18 July 1999
 MOURA L
 NESETRIL Jaroslav, ed

Department of Computer Science, University of Toronto, Toronto, M5S 3G4, Canada

ESA '99 : annual European symposium, 7 (Prague CZE) 1999-07-16

Journal: Lecture notes in computer science,

1999, 1643 462-475

ISBN: 3-540-66251-0 ISSN: 0302-9743 Availability:

INIST-16343; 354000084545070380

No. of Refs.: 18 ref.

Document Type: P (Serial); C (Conference Proceedings) ; A (Analytic)

Country of Publication: Germany; United States

Language: English

We propose a new algorithmic technique for constructing combinatorial designs such as t-designs and packings. The algorithm is based on polyhedral theory and employs the well-known branch-and-cut approach. Several properties of the designs are studied and used in the design of our algorithm. A polynomial-time separation algorithm for clique facets is developed for a class of designs, and an isomorph rejection algorithm is employed in pruning tree branches. Our implementation is described and experimental results are analysed.

English Descriptors: Combinatorial optimization; Bin **packing** problem ; **Steiner tree** problem; Randomised algorithms; Algorithm analysis; Algorithm performance

French Descriptors: Optimisation combinatoire; Probleme remplissage; Probleme arbre Steiner; Algorithme randomise; Analyse algorithme; Performance algorithme

Classification Codes: 001D02A05; 001D01A04

16/5,K/37 (Item 5 from file: 144) **Links**

Fulltext available through: SpringerLink   USPTO Full Text Retrieval Options

Pascal

12578029 · PASCAL No.: 96-0262972

Packing Steiner trees : a cutting plane algorithm and computational results

GROETSCHEL M; MARTIN A; WEISMANTEL R

Konrad-Zuse-Zentrum fuer Informationstechnik Berlin, Takustrasse 7, 14195 Berlin, Germany

Journal: Mathematical programming,

1996, 72 (2) 125-145

ISSN: 0025-5610   CODEN: MHPGA4 Availability: INIST-15655 ; 354000043517070020

No. of Refs.: 22 ref.

Document Type: P (Serial) ; A (Analytic)

Country of Publication: Netherlands

Language: English

In this paper we describe a cutting plane algorithm for the **Steiner tree packing** problem. We use our algorithm to solve some switchbox routing problems of VLSI-design and report on our computational experience. This includes a brief discussion of separation algorithms, a new LP-based primal heuristic and implementation details. The paper is based on the polyhedral theory for the **Steiner tree packing** polyhedron developed in our companion paper (this issue) and meant to turn this theory into an algorithmic tool for the solution of practical problems.

English Descriptors: Graph theory; Trees (mathematics); Polyhedron; Algorithms; Cutting plane method; Separation; Routing; VLSI circuits; Steiner tree problem

French Descriptors: Theorie graphe; Arbre(mathematiques); Polyedre; Algorithme; Methode plan secant; Separation; Acheminement; Circuit VLSI; Probleme arbre Steiner

Classification Codes: 001D01A04

Packing Steiner trees : a cutting plane algorithm
and computational results
In this paper we describe a cutting plane algorithm for the
Steiner tree packing problem. We use our algorithm to
solve some switchbox routing problems of VLSI-design and...
... primal heuristic and implementation details. The paper is based on the
polyhedral theory for the **Steiner tree packing**
polyhedron developed in our companion paper (this issue) and meant to turn
this theory into...

16/5,K/38 (Item 6 from file: 144) <u>Links</u>
Fulltext available through: <u>SpringerLink</u>   <u>USPTO Full Text Retrieval Options</u>
Pascal

Packing Steiner trees : polyhedral investigations
GROETSCHEL M; MARTIN A; WEISMANTEL R
Konrad-Zuse-Zentrum fuer Informationstechnik Berlin, Takustrasse 7, 14195
Berlin, Germany
Let $G = (V, E)$ be a graph and T subset $= V$ be a node set. We call an edge
set S a Steiner tree for T if S connects all pairs of nodes in T. In this
paper we address the following problem, which we call the weighted
Steiner tree packing problem. Given a graph $G = (V, E)$
with edge weights w_e , edge capacities c_e , e element of E, and
node sets $T_1,...,T_N$, find edge sets $S_1,...,S_N$ such
that each S_k is a Steiner tree for T_k , at most c_e of these
edge sets use edge e for each e element of E, and the sum of the weights of
the edge sets is minimal. Our motivation for studying this problem arises
from a routing problem in VLSI-design, where given sets of points have to
be connected by wires. We consider the **Steiner tree**
packing problem from a polyhedral point of view and define an
associated polyhedron, called the **Steiner tree packing**
polyhedron. The goal of this paper is to (partially) describe this
polyhedron by means of inequalities. It turns out that, under mild
assumptions, each inequality that defines a facet for the (single) Steiner
tree polyhedron can be lifted to a facet-defining inequality for the
Steiner tree packing polyhedron. The main emphasis of
this paper lies on the presentation of so-called joint inequalities that
are valid and facet-defining for this polyhedron. Inequalities of this kind
involve at least two Steiner trees. The classes of inequalities we have
found form the basis of a branch & cut algorithm. This algorithm is
described in our companion paper (in this issue).
English Descriptors: Graph theory; Trees (mathematics); Polyhedron;
  Inequality; Facet; Algorithms; Cutting plane method; Steiner tree problem
French Descriptors: Theorie graphe; Arbre(mathematiques); Polyedre;
  Inegalite; Facette; Algorithme; Methode plan secant; Probleme arbre
  Steiner
Classification Codes: 001D01A04

Packing Steiner trees : polyhedral investigations
... in T. In this paper we address the following problem, which we call
the weighted **Steiner tree packing** problem. Given a
graph $G = (V, E)$ with edge weights w_e , edge capacities...
... design, where given sets of points have to be connected by wires. We
consider the **Steiner tree packing** problem from a

polyhedral point of view and define an associated polyhedron, called the
Steiner tree packing polyhedron. The goal of this
paper is to (partially) describe this polyhedron by means of...
... the (single) Steiner tree polyhedron can be lifted to a facet-defining
inequality for the **Steiner tree packing** polyhedron.
The main emphasis of this paper lies on the presentation of so-called joint

...

16/5,K/39 (Item 1 from file: 34) **Links**
  Fulltext available through: USPTO Full Text Retrieval Options
10137620 **Genuine Article#: 489JW Number of References: 23**
A branch-and-price algorithm for the Steiner tree packing problem
Author: Jeong GW; Lee K; Park S (REPRINT) ; Park K
Corporate Source: Korea Adv Inst Sci & Technol,Dept Ind Engn, Yusong Gu,373-1 Gusong Dong/Taejon 305701//South Korea/ (REPRINT); Korea Adv Inst Sci & Technol,Dept Ind Engn, Yusong Gu,Taejon 305701//South Korea/; Elect & Telecommun Res Inst,Yusong Gu,Taejon 303350//South Korea/; Korea Telecom,Telecommun Networks Lab, Yusong Gu,Taejon 305390//South Korea/
Journal: COMPUTERS & OPERATIONS RESEARCH , 2002 , V 29 , N3 (MAR) , P 221-241
ISSN: 0305-0548 **Publication date:** 20020300
Publisher: PERGAMON-ELSEVIER SCIENCE LTD , THE BOULEVARD, LANGFORD LANE, KIDLINGTON, OXFORD OX5 1GB, ENGLAND
Language: English **Document Type:** ARTICLE
Geographic Location: South Korea
Journal Subject Category: COMPUTER SCIENCE, INTERDISCIPLINARY APPLICATIONS; ENGINEERING, INDUSTRIAL; OPERATIONS RESEARCH & MANAGEMENT SCIENCE
Abstract: This paper deals with the **Steiner tree packing** problem. For a given undirected graph $G = (V, E)$ with positive integer capacities and non-negative weights on its edges, and a list of node sets (nets), the problem is to find a connection of nets which satisfies the edge capacity limits and minimizes the total weights. We focus on the switchbox routing problem in knock-knee model and formulate this problem as an integer programming using Steiner tree variables. We develop a branch-and-price algorithm. The algorithm is applied on some standard test instances and we compare the performances with the results using cutting-plane approach. Computational results show that our algorithm is competitive to the cutting plane algorithm presented by Grotschel et al. and can be used to solve practically sized problems.
Descriptors--Author Keywords: Steiner tree packing problem (STP) ; VLSI design ; branch-and-price ; column generation
Cited References:
  BARNHART C, 1998, V46, P316, OPER RES
  BRADY M, 1984, V2, P245, ADV COMPUTING RES
  BURSTEIN M, 1986, V4, P133, ADV CAD VLSI
  BURSTEIN M, 1983, V2, P223, IEEE T COMPUT AID D
  COHOON JP, 1988, V7, P684, IEEE T COMPUT AID D
  DREYFUS SE, 1972, V1, P195, NETWORKS
  ERICKSON RE, 1987, V12, P634, MATH OPER RES
  GAREY MR, 1972, V32, P826, SIAM J APPL MATH
  GROTSCHEL M, 1996, V72, P125, MATH PROGRAM
  GROTSCHEL M, 1996, V72, P101, MATH PROGRAM
  HWANG FK, 1992, V22, P55, NETWORKS
  JOHNSON EL, 1993, V62, P133, MATH PROGRAM
  KARP RM, 1972, P85, COMPLEXITY COMPUTER
  KRAMER MR, 1984, V2, P129, ADV COMPUT RES
  LENGAUER T, 1990, COMBINATORIAL ALGORI
  LIPSKI W, 1984, V2, P231, ADV COMPUTING RES
  LUK WK, 1985, V3, P129, INTEGRATION
  NEMHAUSER GL, 1988, INTEGER COMBINATORIA
  PARK K, 1996, V42, P1277, MANAGE SCI
  SAIT M, 1995, VLSI PHYSICAL DESIGN
  SARRAFZADEH M, 1987, V6, P503, IEEE T COMPUT AID D
  SAVELSBERGH M, 1997, V45, P831, OPER RES
  WINTER P, 1987, V17, P129, NETWORKS
A branch-and-price algorithm for the Steiner tree packing problem
Abstract: This paper deals with the Steiner tree packing problem. For a given undirected graph $G = (V, E)$ with positive integer capacities and non...

16/5,K/40 (Item 2 from file: 34) **Links**
  Fulltext available through: USPTO Full Text Retrieval Options

Abstract: This paper investigates the global routing problem for integrated circuits. We introduce a formulation on the basis of integer programming which minimizes the routing area among a limited set of Steiner trees for each net. Indeed, the involved cost function depends on the channel density of the routing which has a direct influence on the routing area.

Our methods for solving the global routing problem employ local search heuristics, sequential routing, genetic routing, and randomized procedures. Our methods for computing lower bounds are based on linear and Lagrange relaxation. An analysis on the tightness of the bounds indicates that the difference between the cost of the optimal integer solutions and the cost of the optimal fractional solutions is only a small number of tracks in practice. Moreover, the analysis leads to the concept of linear preprocessing by which we exclude a large number of high-cost solutions.

We introduce several versions of preprocessing, one of which preserves the opportunity of obtaining a globally optimal solution in general; all of them do so in practice. Linear preprocessing enables us to solve problem instances with several thousand nets provably optimal or at least provably close to optimal.

All methods have been implemented in the software package ERIDANUS. We present computational results.

The global routing problem assumes the placement of the chip components to be fixed. An extension of the problem, which we call global layout of integrated circuits, allows the placement to be variable and searches for a placement that minimizes the routing area among a limited set of alternatives. We show that the results concerning the global routing problem can be easily extended to global layout.

Descriptors--Author Keywords: routing ; integer programming ; integrated circuits ; combinatorial optimization
Identifiers-- KeyWord Plus(R): PACKING STEINER TREES; ROUTER; ALGORITHM; DESIGN

Cited References:
BURSTEIN M, 1983, V2, P223, IEEE T COMPUT AID D
BURSTEIN M, 1983, P45, P VLSI 83
CARDEN RC, 1996, V15, P208, IEEE T COMPUT AID D
CARDEN RC, 1991, P316, 28TH P DES AUT C
CHIANG C, 1990, V9, P1318, IEEE T COMPUT AID D
CHIANG C, 1994, V13, P1461, IEEE T COMPUT AID D
CHIANG C, 1989, P2, P INT C COMP AID DES
DAI WM, 1987, V6, P828, IEEE T COMPUT AID D
ESBENSEN H, 1994, P428, P EUR DES AUT C GREN
ESBENSEN H, 1994, P402, P EUR DES TEST C PAR
GROTSCHEL M, 1996, V17, P39, EUR J COMBIN
GROTSCHEL M, 1996, V72, P101, MATH PROGRAM
GROTSCHEL M, 1996, V72, P125, MATH PROGRAM
GROTSCHEL M, 1997, V78, P265, MATH PROGRAM
GROTSCHEL M, 1996, V9, P233, SIAM J DISCRETE MATH
HEISTERMAN J, 1991, V10, P748, IEEE T COMPUT AID D
HOLLAND JH, 1975, ADAPTATION NATURAL A
HU TC, 1969, INTEGER PROGRAMMING
HU TC, 1985, P144, VLSI CIRCUIT LAYOUT
KARMARKAR N, 1984, V4, P373, COMBINATORICA
KARP RM, 1987, V2, P113, ALGORITHMICA
KARP RM, 1972, P85, COMPLEXITY COMPUTER
KHACHIAN LG, 1979, V20, P191, SOV MATH DOKL
KORTE B, 1990, P185, PATHS FLOWS VLSI LAY
KRAMER MR, 1984, V2, P129, ADV COMPUT RES
LENGAUER T, 1993, V12, P802, IEEE T COMPUT AID D
LENGAUER T, 1993, V2, P167, LECT NOTES SERIES CO
LENGAUER T, 1990, TEUBNERWILEY SERIES
LUK WK, 1987, V6, P518, IEEE T COMPUT AID D
NG APC, 1987, V6, P229, COMPUT ARTIF INTELL
RAGHAVAN P, 1991, V6, P73, ALGORITHMICA
RAGHAVAN P, 1987, V7, P365, COMBINATORICA
RAGHAVAN P, 1988, V37, P130, J COMPUT SYST SCI
SHAHROKHI F, 1990, V37, P318, J ASSOC COMPUT MACH
SHRAGOWITZ E, 1987, V5, P3, INTEGRATION
TING BS, 1983, V2, P301, IEEE T COMPUT AID D
VANNELLI A, 1991, V10, P193, IEEE T COMPUT AID D
ZIMMERMANN G, 1986, V2, P185, ADV CAD VLSI
ZIMMERMANN G, 1988, P60, 25TH P DES AUT C

Identifiers-- ...PACKING STEINER TREES; ROUTER; ALGORITHM; DESIGN

16/5,K/41 (Item 3 from file: 34) **Links**
   Fulltext available through: SpringerLink   USPTO Full Text Retrieval Options
SciSearch(R) Cited Ref Sci
08567304   **Genuine Article#: 302AR   Number of References: 8**
Gaps in convex disc packings with an application to 1-Steiner Minimum Trees
Author: Swanepoel KJ (REPRINT)
Corporate Source: UNIV PRETORIA,DEPT MATH & APPL MATH/ZA-0002 PRETORIA//SOUTH AFRICA/ (REPRINT)
Journal: MONATSHEFTE FUR MATHEMATIK , 2000 , V 129 , N3 , P 217-226
ISSN: 0026-9255   **Publication date:** 20000000
Publisher: SPRINGER-VERLAG WIEN , SACHSENPLATZ 4-6, PO BOX 89, A-1201 VIENNA, AUSTRIA
Language: English   **Document Type:** ARTICLE
Geographic Location: SOUTH AFRICA
Subfile: CC PHYS--Current Contents, Physical, Chemical & Earth Sciences
Journal Subject Category: MATHEMATICS
Abstract: We show that if six translates of a convex disc C all touch C, and no two of the translates have interior points in common, then there are never more than two gaps, i.e., consecutive non-touching pairs of translates. We also characterize the configurations where there are two, one or no gaps. This result is then applied to show that the Steiner point in a 1-Steiner Minimum Tree in a normed plane has degree at most five if the unit ball is not an affine regular hexagon (where Steiner points of degree six exist).
Descriptors--Author Keywords: convex disc ; **packing ; Steiner minimal tree ; Steiner minimum tree ;** Hadwiger number
Cited References:
   CIESLIK D, 1991, V22, P291, OPTIMIZATION
   CIESLIK D, 1990, V39, P89, ROSTOCK MATH K
   CIESLIK D, 1998, STEINER MINIMAL TREE
   COLTHURST T, 1993, P23, NETWORK OPTIMIZATION
   GRUNBAUM B, 1961, V11, P215, PAC J MATH
   ROBINS G, 1995, V14, P151, DISCRETE COMPUT GEOM
   RUBINSTEIN JH, 1992, V22, P531, NETWORKS
   ZONG C, 1998, V30, P1, B LOND MATH SOC

16/5,K/42 (Item 4 from file: 34) **Links**
   Fulltext available through: custom link   USPTO Full Text Retrieval Options
SciSearch(R) Cited Ref Sci
08135852   **Genuine Article#: 250FG   Number of References: 19**
Routing through virtual paths in layered telecommunication networks
Author: Dahl G (REPRINT) ; Martin A; Stoer M
Corporate Source: UNIV OSLO,DEPT MATH, POB 1080/N-0316 OSLO//NORWAY/ (REPRINT); KONRAD ZUSE ZENTRUM INFORMAT TECH,/D-10711 BERLIN//GERMANY/; TELENOR,/N-2027 KJELLER//NORWAY/
Journal: OPERATIONS RESEARCH , 1999 , V 47 , N5 (SEP-OCT) , P 693-702
ISSN: 0030-364X   **Publication date:** 19990900
Publisher: INST OPERATIONS RESEARCH MANAGEMENT SCIENCES , 901 ELKRIDGE LANDING RD, STE 400, LINTHICUM HTS, MD 21090-2909
Language: English   **Document Type:** ARTICLE
Geographic Location: NORWAY; GERMANY
Subfile: CC ENGI--Current Contents, Engineering, Computing & Technology;
Journal Subject Category: OPERATIONS RESEARCH & MANAGEMENT SCIENCE
Abstract: We study a network configuration problem in telecommunications where one wants to set up paths in a capacitated network to accommodate given point-to-point traffic demand. The problem is formulated as an integer linear programming model where 0-1 variables represent different paths. An associated integral polytope is studied, and different classes of facets are described. These results are used in a cutting plane algorithm. Computational results for same realistic problems are reported.
Identifiers-- KeyWord Plus(R): **PACKING STEINER TREES; ALGORITHM**
Cited References:
   AHUJA RK, 1993, NETWORK FLOWS THEORY
   APPLEGATE D, 1995, 9505 DIMACS
   BIENSTOCK D, 1998, V81, P177, MATH PROGRAM
   CHARTRAND G, 1986, GRAPHS DIGRAPHS
   GOLDBERG AV, 1988, V35, P921, J ASSOC COMPUT MACH
   GROTSCHEL M, 1996, V72, P101, MATH PROGRAM
   GROTSCHEL M, 1996, V72, P125, MATH PROGRAM
   KRAMER MR, 1984, V2, ADV COMPUTING RES
   LORENTZEN R, 1994, V90, P73, TELEKTRONIKK
   LOVASZ L, 1986, MATCHING THEORY .
   MARTIN A, 1992, 924 ZIB TR
   MENGER K, 1927, V10, P96, FUND MATH

NEMHAUSER G, 1988, INTEGER COMBINATORIA
PADBERG M, 1991, V33, P60, SIAM REV
PARK K, 1994, UNPUB INTEGER PROGRA
PARKER M, 1994, V2, P185, TELECOMMUNICATIONS S
PRIM RC, 1957, V36, P1389, BELL SYST TECH J
SCHRIJVER A, 1986, THEORY LINEAR INTEGE
WEISMANTEL R, 1994, 941 ZIB SC
Identifiers-- ...PACKING STEINER TREES; ALGORITHM

16/5,K/43 (Item 5 from file: 34) **Links**
Fulltext available through: USPTO Full Text Retrieval Options
SciSearch(R) Cited Ref Sci
(c) 2007 The Thomson Corp. All rights reserved.
06879740 Genuine Article#: ZY725 Number of References: 14
Switchbox routing in VLSI design: Closing the complexity gap
Author: Hartmann S (REPRINT) ; Schaffter MW; Schulz AS
Corporate Source: TECH UNIV BERLIN,FACHBEREICH MATH, MA 6-1, STR 17 JUNI 136/D-10623
BERLIN//GERMANY/ (REPRINT)
Journal: THEORETICAL COMPUTER SCIENCE , 1998 , V 203 , N1 (AUG 6) , P 31-49
ISSN: 0304-3975 **Publication date:** 19980806
Publisher: ELSEVIER SCIENCE BV , PO BOX 211, 1000 AE AMSTERDAM, NETHERLANDS
Language: English **Document Type:** ARTICLE
Geographic Location: GERMANY
Subfile: CC ENGI--Current Contents, Engineering, Computing & Technology
Journal Subject Category: COMPUTER SCIENCE, THEORY & METHODS
Abstract: The design of integrated circuits has achieved a great deal of attention in the last decade. In the routing phase, there have survived two unsolved layout problems that are important from both the theoretical and the practical point of view. Up to now, switchbox routing has been known to be solvable in polynomial time when there are only 2-terminal nets, and to be NP-complete in case there exist nets involving at least five terminals. Our main result is that this problem is NP-complete even if no net has more than three terminals. Hence, from the theoretical perspective, the switchbox routing problem is completely settled.
The NP-completeness proof is based on a reduction from a special kind of the satisfiability problem. It also is possible to adopt our construction to channel routing implying that this problem is NP-complete, even if each net does not consist of more than five terminals. This improves upon a result of Sarrafzadeh who proved the NP-completeness in case of nets with no more than six terminals. (C) 1998-Elsevier Science B.V. All rights reserved.
Descriptors--Author Keywords: VLSI design ; switchbox routing ; NP-completeness ; **Steiner tree packing**
Identifiers-- KeyWord Plus(R): CHANNEL
Cited References:
FORMANN M, 1993, V15, P267, J ALGORITHM
GAREY MR, 1979, COMPUTERS INTRACTABI
GROTSCHEL M, 1995, V41, P255, Z OPERATIONS RES
HARTMANN S, 1996, 542 TU BERLIN BERLIN
KORTE B, 1990, P185, PATHS FLOWS VLSI LAY
KRAMER MR, 1984, V2, P129, ADV COMPUT RES
LENGAUER T, 1990, COMBINATORIAL ALGORI
MAREKSADOWSKA M, 1992, V13, P39, INTEGRATION
MEHLHORN K, 1986, V33, P60, J ASSOC COMPUT MACH
MIDDENDORF M, 1993, MANHATTAN CHANNEL RO
MOHRING RH, 1995, V8, P625, HDBK OPER R
OKAMURA H, 1981, V31, P75, J COMB THEORY B
SARRAFZADEH M, 1987, V6, P503, IEEE T COMPUT AID D
SZYMANSKI TG, 1985, V4, P31, IEEE T COMPUT AID D

16/5,K/44 (Item 6 from file: 34) **Links**
Fulltext available through: USPTO Full Text Retrieval Options
SciSearch(R) Cited Ref Sci
(c) 2007 The Thomson Corp. All rights reserved.
04874535 Genuine Article#: UN919 Number of References: 38
PLANAR CLOCK ROUTING FOR HIGH-PERFORMANCE CHIP AND PACKAGE CO-DESIGN
Author: ZHU Q; DAI WWM
Corporate Source: INTEL CORP,INTEL DEV LABS/SANTA CLARA//CA/95062; UNIV CALIF SANTA CRUZ,DEPT
COMP ENGN/SANTA CRUZ//CA/95064
Journal: IEEE TRANSACTIONS ON VERY LARGE SCALE INTEGRATION (VLSI) SYSTEMS , 1996 , V 4 , N2 (JUN) ,
P 210-226
ISSN: 1063-8210
Language: ENGLISH **Document Type:** ARTICLE
Geographic Location: USA
Subfile: SciSearch; CC ENGI--Current Contents, Engineering, Technology & Applied Sciences
Journal Subject Category: ENGINEERING, ELECTRICAL & ELECTRONIC; COMPUTER SCIENCE, HARDWARE &
ARCHITECTURE

Abstract: A new concept of chip and package co-design for the clock network is presented in this paper, We propose a two-level clock distribution scheme which partitions the clock network into two levels, First, the clock terminals are partitioned into a set of clusters, For each cluster, a local on-chip clock tree is used to distribute the clock signal from a locally inserted buffer to terminals inside this cluster, The clock signal is then distributed from the main clock driver to each of local buffers by means of a global clock tree, which is a planar tree with equal path lengths, With the hip chip area I/O. attachment, the planar global clock tree can be put on a dedicated package layer, The interconnect on the package layer has two to four order smaller resistance than that on the chip layer, The main contribution of this paper is a novel algorithm to construct a planar clock tree with equal path lengths-the length of the path from the clock source to each destination is exactly the same, In addition, the path length from the source to destinations is minimized.
Descriptors--Author Keywords: CLOCK DISTRIBUTION ; CLOCK ROUTING ; CLOCK TREE ; CHIP AND PACKAGE . CO-DESIGN ; HIP CHIP ; INTERCONNECT ; **PACKAGE** ; PLANAR ROUTING ; **STEINER TREE**
Research Fronts: 94-5198 001 (PERFORMANCE-DRIVEN GLOBAL ROUTING ALGORITHM FOR GATE ARRAY; RISC WORKSTATION PACKAGING)

Cited References:
ANCEAU F, 1982, V17, P51, IEEE J SOLID STATE C
BOESE KD, 1993, P182, P 30 DES AUT C
BOESE KD, 1992, P17, P 5 IEEE INT C ASIC
BORAH M, 1994, V13, P1563, IEEE T COMPUT AID D
CHAO TH, 1992, V39, P799, IEEE T CIRCUITS-II
CHOU NC, 1993, P552, TECH DIG PAP IEEE IN
CONG J, 1990, V12, P1157, IEEE T COMPUT AID D
EDAHIRO M, 1993, P612, P 30 ACM IEEE DES AU
EDAHIRO M, 1994, P1, P 31 ACM IEEE DES AU
ELMORE WC, 1948, V19, P55, J APPL PHYS
FISHBURN JP, 1990, V39, P945, IEEE T COMPUT
FISHER AL, 1985, V34, P734, IEEE T COMPUT
FRYE RC, 1993, V10, P8, IEEE DES TEST COMPUT
FRYE RC, 1994, V17, P30, IEEE T COMPON PACK B
HO JM, 1990, V9, P185, IEEE T COMPUT AID D
HO JM, 1989, P161, P 26 ACM IEEE DES AU
JACKSON MAB, 1990, P573, P 27 DES AUT C
KAHNG A, 1991, P322, P 28 DES AUT C
KAHNG AB, 1992, V11, P893, IEEE T COMPUT AID D
KAHNG AB, 1994, P440, P EUR DES AUT C
KAHNG AB, 1994, P213, TECH DIG PAPERS IEEE
KHAN W, 1993, TR9308 W MICH U COMP
LI YM, 1992, P458, TECH DIG PAP IEEE IN
LIAO H, 1993, P726, P 30 ACM IEEE DES AU
LU Y, 1991, THESIS U CALIFORNIA
OHTSUKI T, 1986, V4, CH9, ADV CAD VLSI
OHTSUKI T, 1985, P INT C CIRC SYST CH
PREPARATA FP, 1985, COMPUTATIONAL GEOMET
PULLELA S, 1994, P556, TECH DIG PAP IEEE IN
TELLEZ GE, 1994, P219, TECH DIG PAP IEEE IN
TSAY RS, 1993, V12, P242, IEEE T COMPUT AID D
TSAY RS, 1991, P336, TECH DIG PAP IEEE IN
WANN DF, 1983, V32, P284, IEEE T COMPUT
XI JG, 1995, P4891, P 32 DES AUT C
ZHU Q, 1994, LSI LOGIC CORP
ZHU Q, 1992, P473, TECH DIG PAP IEEE IN
ZHU Q, 1992, P628, TECH DIG PAP IEEE IN
ZHU Q, 1994, UCSCCRL9439 U CAL SA

16/5,K/45 (Item 7 from file: 34) <u>Links</u>
Fulltext available through: <u>USPTO Full Text Retrieval Options</u>
04547891 **Genuine Article#: TR447 Number of References: 11**
PACKING STEINER TREES - FURTHER FACETS

Author: GROTSCHEL M; MARTIN A; WEISMANTEL R
Corporate Source: KONRAD ZUSE ZENTRUM BERLIN/D-10711 BERLIN//GERMANY/
Language: ENGLISH Document Type: ARTICLE
Geographic Location: GERMANY
Subfile: SciSearch
Journal Subject Category: MATHEMATICS
Abstract: In this paper we continue the investigations in [3] for the **Steiner tree packing** polyhedron. We present several new classes of valid inequalities and give sufficient (and necessary) conditions for these inequalities to be facet-defining. It is intended to incorporate these inequalities into an existing cutting plane algorithm that is applicable to practical

problems arising in the design of electronic curcuits. (C) 1995 Academic Press Limited
Identifiers-- KeyWords Plus: CHANNEL
Cited References:
    FORMANN M, 1993, V15, P267, J ALGORITHM
    FRANK A, 1990, P47, PATHS FLOWS VLSI LAY
    GROTSCHEL M, 1992, SC928 PREPR
    GROTSCHEL M, 1992, SC929 PREPR
    KRAMER MR, 1984, V2, P129, ADV COMPUT RES
    LENGAUER T, 1990, COMBINATORIAL ALGORI
    MARTIN A, 1993, V6, P185, CWJ Q
    MARTIN A, 1992, THESIS TU BERLIN
    SARRAFZADEH M, 1987, V6, P503, IEEE T COMPUT AID D
    SCHRIJVER A, 1990, P329, PATHS FLOWS VLSI LAY
    SCHRIJVER A, 1986, THEORY LINEAR INTEGR
PACKING STEINER TREES - FURTHER FACETS

Abstract: In this paper we continue the investigations in [3] for the Steiner tree packing polyhedron. We present several new classes of valid inequalities and give sufficient (and necessary) conditions...

16/5,K/46 (Item 1 from file: 434) <u>Links</u>
SciSearch(R) Cited Ref Sci
08632995 Genuine Article#: M2796 Number of References: 32
GREEDY - A NEW STARTING SET PROCEDURE
Author: SCHAGEN JD; SCHENK H
Corporate Source: UNIV AMSTERDAM,CRYSTALLOG LAB,NIEUWE ACHTERGRACHT 166/1018 WV
AMSTERDAM//NETHERLANDS/
Journal: ZEITSCHRIFT FUR KRISTALLOGRAPHIE , 1987 , V 179 , N1-4 , P 97-111
Language: ENGLISH Document Type: ARTICLE
Geographic Location: NETHERLANDS
Subfile: SciSearch; CC PHYS--Current Contents, Physical, Chemical & Earth Sciences
Journal Subject Category: CRYSTALLOGRAPHY
Research Fronts: 86-1145 001 (MULTIWAVELENGTH ANOMALOUS DIFFRACTION DATA IN MACROMOLECULAR
CRYSTALLOGRAPHY; RECOVERING PHASE INFORMATION; INTERSTITIAL RETINOL- BINDING PROTEIN (IRBP))
 86-5811 001 (STEINER MINIMAL-TREES; COMBINATORIAL OPTIMIZATION; MINIMAL SPANNING TREE)
Cited References:
    COCHRAN W, 1955, V8, P1, ACTA CRYSTALLOGR
    EDMONDS J, 1971, P127, MATH PROGRAMMING
    FORTIER S, 1979, V35, P2062, ACTA CRYSTALLOGR B
    GERMAIN G, 1971, V27, P368, ACTA CRYSTALLOGR A
    GERMAIN G, 1970, V26, P274, ACTA CRYSTALLOGR B
    GILLIS J, 1948, V1, P174, ACTA CRYSTALLOGR
    HALL SR, 1985, V18, P263, J APPL CRYSTALLOGR
    HASEK J, 1983, P260, 8TH ECM
    HULL SE, 1978, V34, P38, ACTA CRYSTALLOGR A
    KARLE J, 1956, V9, P635, ACTA CRYSTALLOGR
    KARLE J, 1966, V21, P849, ACTA CRYSTALLOGR
    KRUSKAL JB, 1956, V7, P48, P AM MATH SOC
    LAWLER EL, 1976, P264, COMBINATORINAL OPTIM
    LESSINGER L, 1976, V32, P538, ACTA CRYSTALLOGR A
    MAIN P, 1977, V33, P750, ACTA CRYSTALLOGR A
    MAIN P, 1985, P206, CRYSTALLOGRAPHIC COM
    MOTHERWELL WDS, 1976, V27, P681, ACTA CRYSTALLOGR A
    OVERBEEK AR, 1978, P108, COMPUTING CRYSTALLOG
    PONTENAGEL WMG, 1983, P96, THESIS U UTRECHT
    SCHENK H, 1973, V29, P77, ACTA CRYSTALLOGR A
    SCHENK H, 1973, V29, P503, ACTA CRYSTALLOGR A
    SCHENK H, 1971, V27, P185, ACTA CRYSTALLOGR B
    SCHENK H, 1971, V27, P667, ACTA CRYSTALLOGR B
    SCHENK H, 1972, V28, P538, ACTA CRYSTALLOGR B
    SCHENK H, 1972, V28, P625, ACTA CRYSTALLOGR B
    SCHENK H, 1972, V1, P143, CRYST STRUCT COMMUN
    SCHENK H, 1985, P200, CRYSTALLOGRAPHIC COM
    SCHENK H, 1970, V56, P4937, TETRAHEDRON LETT
    SHELDRICK GM, 1976, P184, CRYSTALLOGRAPHIC COM
    STAM CH, 1972, V28, P2936, ACTA CRYSTALLOGR B
    WELSH DJA, 1971, P357, MATROID THEORY
    WHITE PS, 1975, V31, P53, ACT CRYST A
Research Fronts: 86-1145 001 (MULTIWAVELENGTH ANOMALOUS DIFFRACTION DATA IN MACROMOLECULAR
CRYSTALLOGRAPHY; RECOVERING PHASE INFORMATION; INTERSTITIAL RETINOL- BINDING PROTEIN (IRBP))

86-5811 001 (STEINER MINIMAL-TREES; COMBINATORIAL OPTIMIZATION; MINIMAL SPANNING TREE)

16/5,K/47 (Item 1 from file: 95) <u>Links</u>
  Fulltext available through: <u>USPTO Full Text Retrieval Options</u>
TEME-Technology & Management
01002709 I96060068226
Planar clock routing for high performance chip and package co-design
(Planares Taktrouting fuer einen Hochleistungschip)
Qing Zhu; Wayne Wei-Ming Dai
Dev. Labs., Intel Corp., Santa Clara, CA, USA
IEEE Transactions on Very Large Scale Integration Systems, v4, n2, pp210-226 , 1996
Document type: journal article Language: English
Record type: Abstract
ISSN: 1063-8210
Abstract:
A new concept of chip and package co-design for the clock network is presented in this paper. We propose a two level clock distribution scheme which partitions the clock network into two levels. First, the clock terminals are partitioned into a set of clusters. For each cluster, a local on-chip clock tree is used to distribute the clock signal from a locally inserted buffer to terminals inside this cluster. The clock signal is then distributed from the main clock driver to each of local buffers by means of a global clock tree, which is a planar tree with equal path lengths. With the flip chip area I/O attachment, the planar global clock tree can be put on a dedicated package layer. The interconnect on the package layer has two to four order smaller resistance than that on the chip layer. The main contribution of this paper is a novel algorithm to construct a planar clock tree with equal path lengths-the length of the path from the clock source to each destination is exactly the same. In addition, the path length from the source to destinations is minimized.
Descriptors: GRAND SCALE INTEGRATION; CIRCUIT CAD; INTEGRATED CIRCUIT PACKAGING; CHIPS–SEMICONDUCTORS; CLOCK FREQUENCY; CLUSTER FORMING; FLIP CHIP DEVICES; I O UNIT; ALGORITHM; DIGITAL ICS; TREE STRUCTURE; NETWORK STUCTURE–ELECTRIC; INTEGRATED CIRCUIT DESIGN; INTEGRATED CIRCUIT INTERCONNECTIONS; NETWORK ROUTING
Identifiers: PLANAR CLOCK ROUTING; TWO LEVEL CLOCK DISTRIBUTION SCHEME; LOCAL ON CHIP CLOCK TREE; LOCALLY INSERTED BUFFER; CLOCK DRIVER; LOCAL BUFFERS; GLOBAL CLOCK TREE; EQUAL PATH LENGTHS; DEDICATED **PACKAGE** LAYER; **STEINER TREE**; TAKTSIGNALVERTEILUNG; Taktrouting; Hochleistungs-Chip
Identifiers: ...TREE; LOCALLY INSERTED BUFFER; CLOCK DRIVER; LOCAL BUFFERS; GLOBAL CLOCK TREE; EQUAL PATH LENGTHS; DEDICATED **PACKAGE** LAYER; **STEINER TREE**; TAKTSIGNALVERTEILUNG; Taktrouting; Hochleistungs-Chip